

AB305N

LED beacon, white base, white lens

General

The AB305N is a general purpose red LED beacon which can be used in various applications. Utilising modern LED components to provide a high level of visual indication and offering longer expected component life.

Greater visibility

The AB305N beacon is fitted with a diffuser for greater visibility and spread of light.

Locking mechanism

The mechanism for locking the beacon to the base is activated by default, but can be disabled if required. A special tool is required to remove the beacon from the base, if the locking mechanism is active.



Einzelheiten

- Interfere-less safety locking head to base
- Weather proof / IP65
- 12V to 30 VDC
- Long life LED design
- White high quality polycarbonate housing
- Removable connection terminal

AB305N

LED beacon, white base, white lens

Technische Spezifikationen

Allgemein

Zubehörgruppe	Leuchtfeuer
Typ	Zubehör

Flash-Spezifikationen

Blitzfrequenz	1 Hz
---------------	------

Elektrische Angaben

Betriebsspannung	10 to 30 VDC
Aktueller Verbrauch	30 mA

Physikalisch

Abmessungen	85 x 81 mm (Ø x D)
Liefergewicht	144 g
Material	Hochschlagfestes Polycarbonat

Umweltbedingungen

Betriebstemperatur	-20 to 60°C
IP Klassifizierung	IP65

Regulativ

Kompatibilität	CE
----------------	----