SH-62-0211-0001-99

SmartCell Wireless Remote Indicator (Fire Detection Indicator Text)

Overview

The SmartCell wireless remote indicator is quick and easy to install and offers individual addressing at the Excellence control panel or Gateway.

Features include red fire indication LED, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the Excellence wireless gateway.



Details

- Fully wireless
- Quick and easy to install
- Red fire indication LED
- Unique design
- Inbuilt locking mechanism

SH-62-0211-0001-99

SmartCell Wireless Remote Indicator (Fire Detection Indicator Text)

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	Excellence Gateway

Electrical

Power supply type	Batteries
Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)
Power consumption	1.46 W max.
Operating voltage	2.7 to 3.65 VDC
Current consumption	0.1 to 400 mA

Physical

Physical dimensions	110 x 39 mm (Ø x D)
Colour	White
Mounting type	Wall mount
Mounting base	Wireless

Environmental

Vandal proof	Yes
Operating temperature	-10 to +55 °C
Storage temperature	-10 to +30 °C (with batteries)
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP21C

Regulatory

Compliancy	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR
Standards	EN54-13 EN54-25

Compatible products

Category	Reference	Description
Batteries	SH-836-000	
Interface unit	SH-14-3201-000 1-99	
Test Equipment	SH-21-BASE-020 0	

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 May 2026 - 10:41