



AD68-0200

Alarmline II Digital LHD Cable 68°C (155°F) w/ PVC Sheath - 200m

General

The AD68-0200 is a Digital Linear Heat Detection (LHD) cable with a 68°C (155°F) fixed temperature activation rating. It has a PVC outer sheath for increased chemical protection in caustic environments and is supplied in 200m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

In addition to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge', 'A', 'P', and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD68-0200

Alarmline II Digital LHD Cable 68°C (155°F) w/ PVC Sheath - 200m

Technical specifications

Electrical

Operating voltage	0 to 30 VAC
	0 to 42 VDC
No. of cable cores	2

Conductor

Resistance	~100 ohms/km per leg (30.4 ohms/Kft)
Capacitance	88 to 150 pF/m
Inductance	540 to 1050 nH/m

Physical

Physical dimensions	3.60 mm $\pm$ 0.12 mm (nominal outside diameter)
Net weight	4.08 kg
Colour	Red
Mounting type	Cable mount

Environmental

Operating temperature	45°C (113°F)
Relative humidity	0 to 100% noncondensing
Environment	Indoor, Outdoor

Regulatory

Compliance	RoHS
Certification	CE, FM, UL