

DM970

Pulsador analógico manual intrínsecamente seguro. Rojo.

General

The DM970 is an intrinsically safe manual call point. It should be used together with the PT971/2 protocol translator and GBX70 barrier. It is based on a standard weatherproof manual call point and features an "interrupt" facility to provide fast response to an alarm.

Application

When activated, the intrinsically safe call point interrupts the polling cycle to indicate to the control panel that it has been operated. Because of this feature, an alarm can be reported in less than 0.2 seconds.

The DM970 has the same operating characteristics as the standard manual call point versions. It is a red, break-glass call point to which a protective lift-up flap may be added as an option.



Detalles

- Easy to install
- May be used with break glass or resettable element
- Easy to replace glass
- High quality micro switch
- Back box included
- IP67 rated
- BASEEFA certified

DM970

Pulsador analógico manual intrínsecamente seguro. Rojo.

Especificaciones técnicas

General

Status indication	Red Alarm LED
-------------------	---------------

Eléctrico

Voltaje de funcionamiento	14 to 22 VDC
Current consumption	230 µA (Quiescent) 4 mA (Alarm)

Físico

Dimensiones físicas	124 x 124 x 60 mm
Net weight	± 400 g
Colour	Rojo

Medioambiental

Operating temperature	-20 to +40°C (T5) / -20 to +60°C (T4)
Temperatura de almacenamiento	-30 to +80°C
Humedad relativa	0 to 95% noncondensing
Environment	Interior, IS
IP rating	IP67

Regulador

Certificación	EN54-11
---------------	---------

Regulatory

BASIEFA	BAS02ATEX1290
Classification	E Ex ia IIc T5



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 18 February 2025 - 11:37