



AD88SS-0500

Alarmline II Digital LHD Cable 88°C (190°F), SS over PVC Sheath, 500 m

General

The AD88SS-0500 is a Digital Linear Heat Detection (LHD) cable with a 88°C (190°F) fixed temperature activation rating. It has a Stainless steel over PVC outer sheath for increased mechanical protection and is supplied in 500m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' , 'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Yksityiskohdat

- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD88SS-0500

Alarmline II Digital LHD Cable 88°C (190°F), SS over PVC Sheath, 500 m

Tekniset tiedot

Sähkö-

Operating voltage	0 to 30 VAC, 0 to 42 VDC
-------------------	--------------------------

Kaapelisydämien määrä	2
-----------------------	---

Kapellimestari

Vastus	~100 ohms/km per leg (30.4 ohms/Kft)
--------	--------------------------------------

Kapasitanssi	88 to 150 pF/m
--------------	----------------

Induktanssi	540 to 1050 nH/m
-------------	------------------

Fyysinen

Physical dimensions	4.1mm ± 0.12mm (Nominal Outside diameter)
---------------------	---

Net weight	14.6 kg
------------	---------

Colour	Hopea
--------	-------

Asennustyyppi	Kaapelikiinnitys
---------------	------------------

Ympäristö-

Operating temperature	69°C (156°F) (max. Ambient)
-----------------------	-----------------------------

Relative humidity	0 to 100% noncondensing
-------------------	-------------------------

Environment	Sisällä, Ulkoilma
-------------	-------------------

Säätely

Sertifiointi	CE
--------------	----