9-30780-KID-EN

Kidde ModuLaser, Minimum display module

General

ModuLaser is a scalable aspirating smoke detection solution that makes installation easier, maintenance quicker, and takes applications further than traditional air sampling detectors. Two basic module types comprise the ModuLaser solution: a display module, and a detector module. Each detector module can accommodate up to 250 meters combined sampling pipe. Display modules and detector modules communicate by RS-485 interconnections.

Display modules are available in three configurations: Standard with TFT color display, status LED's and navigation buttons, Minimum with only status LED's, and Command which is similar to the Standard but with the added functionality to control various modules over SenseNET. The Minimum and Standard Display Modules can each support up to 8 detector modules, while the Command Display Module can support up to 127 modules across the SenseNET network.

Minimum display module

The ModuLaser Minimum Display Module offers a cost effective alternative to the Standard Display Module. While the Standard Display Module features a user interface which consist of a TFT color display, navigation buttons and status LED’s, the Minimum Display Module only features status LED’s. Depending on the requirements of the installation, only having status LED’s might be sufficient to locally indicate faults or alarms while still reporting faults and alarms via the relay outputs or APIC. Due to the absence of a screen and navigation buttons, the Minimum Display Module(and associated detectors modules) must be configured via a computer using Remote software or via SenseNET using a Command Display Module.

Perfect solution

Thanks to advanced features that make it virtually impervious to dust and dirt, ModuLaser is ideal for use in hostile environments that would disable other kinds of smoke detectors. Forward scattering optical detection adds early warning capability without the risk of nuisance alarms normally associated with high sensitivity smoke detection, while exclusive environmental compensation technology adds a high degree of reliability to an already solid detection solution.

Détails

- Modular Design : Separate centrally-controllable detector modules allow efficient piping and discrete zones with no overlap.
- Zoned aspirating smoke detection : Individual detector modules provide detection for individual areas or zones, specific zone alarm information can be transmitted to the main fire alarm panel via a common APIC address card in the display module or through dedicated alarm relays within each detector module.
- Simplified installation : Ingenious docking station design allows detectors to be easily connected together as a group. Sensitive electronics are easily removed to ensure they will not be damaged during first fix installation. Aspirating pipework and cable entries can easily be made into either the top or the bottom of the unit.
- Easy pipe connection : The quick fit pipe adaptor system locks down securely, yet leaves plenty of room for easy pipe connection and removal.
- Quick location of smoke : Each detector module is self-contained, which means no delays in determining in which zone (sampling pipe) smoke is present.
- Universal Status LEDs

9-30780-KID-EN

Kidde ModuLaser, Minimum display module

Spécifications techniques

Général

Indication d'état	LED's
Interface utilisateur	Navigation buttons
Niveaux d'alarme	4, Aux, Pre-alarm, Alarm and Alarm 2
Journal des événements	20.000 events per module
Support RS485	Yes (SenseNET and SenseNET+)
Connectivity	USB (x2), IP and APIC on Display Module

Électrique

Operating voltage	18 to 30 VDC
Current consumption	Display Module (at 24 VDC): 204 mA (Minimum), 232 mA (Standard), 232 mA (Command) Detector Module (at 24 VDC): 260 mA (fan speed 1), 380 mA (fan speed 6, default), 940 mA (fan speed 16)

Détection

Principe de détection	Laser light scattering mass detection and particle evaluation
Gamme de sensibilité aux particules	0.003 to 10 microns

Taux échantillonnage

Longueur	Up to 250 m (820 ft.) combined per detector module
Qté de trous d'échantillonnage	Up to 20 - Class A per detector module Up to 40 - Class B per detector module Up to 50 - Class C per detector module
Taille de l'orifice	27 or 25 mm (1.06 or 0.98 in) outer diameter
Emplacement de l'orifice	Top or bottom
Taille d'échappement	27 or 25 mm (1.06 or 0.98 in) outer diameter
Emplacement d'échappement	Top or bottom

Entrée

Quantité entrée	2 per module
Type d'entrée et classe	Supervised
Résiliation	15 KΩ 5% 1/4 W
Programmable	Yes

Sortie

Output quantity	3 per module
Output type and rating	Voltage free (contact rating 2 A at 30 VDC / NO/NC/C)
Programmable	Yes

Caractéristiques physiques

Physical dimensions	110.5 x 133.5 x 300 mm (4.35 x 5.25 x 11.8 in) (W x D x H)
Net weight	Display Module: 1.18 kg (2.6 lb.) Detector Module: 1.57 kg (3.46 lb.)
Colour	Grey-white (RAL 9002)
Mounting type	Montage en surface
Cable entries	2 at the bottom, 2 at the rear, 2 at the top on Detector Module, and 3 at the top on the Display Module

Environnement

Operating temperature	Equipment: -10 to +60°C (14 to +140°F) Sampled air: -20 to +60°C (-4 to +140°F)
Relative humidity	0 to 95% noncondensing
Environment	Intérieur
IP rating	IP40

Régulateur

Compliancy	REACH, RoHS
Certification	BOSEC, CPR, EN54-20

Physical

Cable entry size	20 mm (0.5 in) - top and bottom
Detector module orientation	Vertical (0 or 180 deg)

Chart recorder

Sampling period	Adjustable between 1 s and 60 s
Capacity	1 months @ 1 s / Up to 5 years @ 60 s
Values recorded	Detector value, 4 alarm level values, flow value and temperature (all simultaneously)

Sampling pipe

Inlet quantity	1 per detector module



KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 23 October 2026 - 11:16