



# ADE68-0200

## AlarmLine II Digital EN LHD cable 68°C, 200 m

### General

---

The ADE68-0200 is a Digital Linear Heat Detection (LHD) cable with a 68°C fixed temperature activation rating. The ADE range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

### Operation

---

The ADE range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable is used in combination with the controller and end-of-line (EOL) unit, and can be connected to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit to signal an alarm condition.

### Alarm location

---

The control unit can identify along the length of the sensor cable where an alarm condition has occurred. The alarm location is then indicated on the display of the controller. Both zone are displayed at the same time.

### Cable fixings for all applications

---

A range of 'edge', 'A', 'P', and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



### Details

---

- EN54-28:2016 approved
- Low-Smoke Zero Halogen
- Up to 1000 m
- Detection along total cable length
- Flame retardant
- Oil resistant
- UV Stable
- Simple low maintenance installation
- RoHS compliant

# ADE68-0200

## AlarmLine II Digital EN LHD cable 68°C, 200 m

### Technische specificaties

---

#### Elektrisch

Bedrijfsspanning	0 to 49 VAC, 0 to 74 VDC
Kabelspecificatie	Insulation 1kV
Aantal kabeladers	2

#### Detectie

Alarmtemperatuur (typisch)	+68°C
----------------------------	-------

#### Geleider

Weerstand	2.5 ohm per m
Capacitantie	<100 pF per m
Inductie	<3.2 uH per m

#### Fysiek

Fysieke afmetingen	Diameter 5.72 mm +/- 0.12 mm (0.225" +/- 0.0005")
Kleur	Rood
Type montage	Kabelbevestiging

#### Omgeving

Bedrijfstemperatuur	-40 to +45°C (Ambient)
Relatieve vochtigheid	0 to 98% noncondensing

#### Regelgeving

Certificering	CE, EN54-28
---------------	-------------