

NC-MCS09-0-Y

Intelligent conventional recess mount manual call point - DISPARO MANUAL SISTEMA DE EXTINCIÓN, 0 Ω (yellow)

General

The NC-MCS09-0-Y is a yellow manual call point for recess mount applications on most industry standard, high quality wall boxes. For surface mount applications an optional, colour matched back box is available.

The call point offers one normally open contact in series with a 0 Ω resistor, as well as a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 style resettable element, pluggable connectors for both contacts, a handy wire bridge to help with cable continuity testing, as well as a test key that doubles up as a service tool for disassembly of the device.

Installation

Installation time and installation flexibility are of paramount importance. The Kidde Commercial MCP range directly meets these needs by providing features designed specifically for this. Pluggable terminal blocks facilitate the pre-connection of all cables. This terminal block is then simply connected to the MCP. Should continuity testing be needed, the handy wire bridge fits neatly into the terminal block in place of the MCP without having to disconnect any cables.

For service and maintenance no additional tools other than the test key is needed. With easy front access in all installations and even with the protection cover fitted, the test key is also used to remove the front cover of the unit should a frangible element need to be replaced.

Options

Both break glass (frangible elements) and re-settable operating elements may be used. The MCP can be configured as either a break glass or re-settable unit by simply changing from one element to another. Other than the optional frangible element, no additional parts are required. Other parts and accessories include colour matched surface mount boxes, recess mount adapters, trim skirts, flip covers, metal test keys and replacement parts.

This range of manual call points is available in various colours with various trigger resistor options to suit most applications. In addition various function markings are available including regional language variants.



Details

- Specifically designed for extinguishing control systems
- Alarm indication by alarm flag
- Enhanced aesthetics with screen printed, high resolution functional marking
- Resettable and also usable with an optional frangible element
- Easy to install (plug and play)
- Various surface and recess mounting options available for installation flexibility
- Protection hinged cover with anti-tamper facilities available for avoiding accidental activation
- Backward compatible adapter available for retrofit applications in existing systems
- Key test facility from the front of the unit for easy access, even when a protection cover is fitted
- Easy service and maintenance with test key disassembly and pluggable connectors

NC-MCS09-0-Y

Intelligent conventional recess mount manual call point - DISPARO MANUAL SISTEMA DE EXTINCIÓN, 0 Ω (yellow)

Technische specificaties

Algemeen

Status indicatie	Alarm flag
Compatibiliteit	Conventional alarm systems
Aansluiting	Hardwired contacts

Elektrisch

Type voeding	VDC
Bedrijfsspanning	10 to 24 VDC
Stroomverbruik	0 mA (Standby)
Kabelspecificatie	0.404 to 2.05 mm (0.13 to 3.31 mm²)
Aantal kabeladers	2
Aansluitingen	7

Detectie

Detectie principe	Manual activation
Bewaking	Activated, Off
Dekkingsgebied	Region specific
Zone lengte	<2 km, CIE specific
Reactietijd	< 3 s
Installatiehoogte	Determined by local regulation

Uitgang

Uitgangshoeveelheid	2
Type uitgang en classificatie	1 x NO resistor limited, 1 x change over relay 1 A @ 24 VDC

Fysiek

Fysieke afmetingen	87 x 87 x 26 mm (W x H x D)
Netto gewicht	101 g
Kleur	Geel (RAL 1003)
Type montage	Back box, Muurmontage
Materiaal (behuizing)	Vlamvertragend ABS
Functionele markering	DISPARO MANUAL SISTEMA DE EXTINCIÓN

Omgeving

Vandalbestendig	Nee
Bedrijfstemperatuur	-10 to +55°C
Opslagtemperatuur	-25 to +70°C
Relatieve vochtigheid	10 to 95% noncondensing
Omgeving	Binnen
IP-classificatie	IP41

Regelgeving

Conformiteit	CE, REACH, RoHS 3, WEEE
Certificering	CE

SKU info

Product series (all languages)	NC-Series
--------------------------------	-----------

Compatibele producten

Categorie	Referentie	Beschrijving
Detectieapparaat N-MC-AFM-Yt		
Detectieapparaat N-MC-BB-Yt		
Detectieapparaat N-MC-FCt		MCP Accessory - Intelligent Manual Call Point Flip Cover
Detectieapparaat N-MC-FEt		MCP Accessory - Intelligent Manual Call Point Frangible Element

