

NC-DBD-W

Conventional standard point detector base with diode (White)

General

The NC-DBD-W is an NC series surface mount first-fix base offering and integrated diode. It allows any NC Series conventional point detector to be inserted, removed or replaced without rewiring using an easy twist and lock action. The integrated diode allows support for BS5839 "head-out" functionality.

The NC-DBD-W supports a remote indicator connection.

Ease of Installation

Forming an integral part of the detector assembly, NC Series standard bases are provided with key-hole slots for screw fixing direct to ceiling structures or conduit boxes. Large rear cable entry allows for easy wiring to the base.

For special applications a base accessory is available for surface installations, ensuring an easy and practical installation.

Ease of Wiring & Testing

Clearly marked terminals ensure correct and secure wiring termination for zone and remote indicator connections.

Ease of Use

Inserting the NC Series detector into the base is accomplished with a simple turn and lock mechanism. To prevent unauthorised removal of a detector from its base, an easy-to-activate locking mechanism is incorporated into all NC series detectors. If activated, a detector can only be released from its base using a dedicated tool.



Details

- Common first-fix mounting base for all white NC-Series detectors
- Pre-installed diode for BS5839 "head-out" support
- A selectable detector locking mechanism protects against unauthorised removal
- Large rear cable entry with ample space for cables
- Flexible installation fixture with first fix screw feature reduces installation time and effort
- Clearly visible terminal marking avoids incorrect cabling
- Robust, wiring terminals for easy installation
- Simple twist-and-lock detector action ensures the detector is properly inserted
- Dual contact points on every connector for reliable detector/base contact

NC-DBD-W

Conventional standard point detector base with diode (White)

Technische specificaties

Algemeen

Compatibiliteit	NC-Series point detectors
Aansluiting	2-wire zone and remote indicator

Elektrisch

Bedrijfsspanning	24 VDC (typical)
Kabelspecificatie	1.0 to 2.1 mm² (17 to 14 AWG) shielded or unshielded twisted-pair
Aantal kabeladers	2 for zone, 2 for remote indicator
Aansluitingen	4

Uitgang

Alarmuitgang op afstand Supported

Fysiek

Fysieke afmetingen	100 x 16.5 mm (Ø x H)
Netto gewicht	45 g
Kleur	Wit (RAL 9016)
Type montage	Plafondmontage
Kabelinvoeren	1
Materiaal (behuizing)	ABS

Omgeving

Vandalbestendig	Nee
Bedrijfstemperatuur	-10 to +65°C
Opslagtemperatuur	-30 to +75°C
Relatieve vochtigheid	10 to 93% (noncondensing)
Omgeving	Binnen

Regelgeving

Conformiteit	CE, UKCA
Standaarden	EN54 (with relevant detector)

Physical

Material (contacts)	Tin-phosphor bronze (QSn6.5-0.1)
---------------------	----------------------------------

Compatibele producten

Categorie	Referentie	Beschrijving
Detectieapparaat	NC-BA-SM-W	
Detectieapparaat	NC-DPH-W	
Detectieapparaat	NC-DPM-W	
Detectieapparaat	NC-DPO-W	

