

DM970

Analoge handbrandmelder, intrinsiek veilig, kleur rood

General

The DM970 is an intrinsically safe manual call point. It should be used together with the PT971/2 protocol translator and GBX70 barrier. It is based on a standard weatherproof manual call point and features an "interrupt" facility to provide fast response to an alarm.

Application

When activated, the intrinsically safe call point interrupts the polling cycle to indicate to the control panel that it has been operated. Because of this feature, an alarm can be reported in less than 0.2 seconds.

The DM970 has the same operating characteristics as the standard manual call point versions. It is a red, break-glass call point to which a protective lift-up flap may be added as an option.



Details

- Easy to install
- May be used with break glass or resettable element
- Easy to replace glass
- High quality micro switch
- Back box included
- IP67 rated
- BASEEFA certified

DM970

Analoge handbrandmelder, intrinsiek veilig, kleur rood

Technische specificaties

Algemeen

Status indicatie	Red Alarm LED
------------------	---------------

Elektrisch

Bedrijfsspanning	14 to 22 VDC
Stroomverbruik	230 μ A (Quiescent) 4 mA (Alarm)

Fysiek

Fysieke afmetingen	124 x 124 x 60 mm
Netto gewicht	$\pm$ 400 g
Kleur	Rood

Omgeving

Bedrijfstemperatuur	-20 to +40°C (T5) / -20 to +60°C (T4)
Opslagtemperatuur	-30 to +80°C
Relatieve vochtigheid	0 to 95% noncondensing
Omgeving	Binnen, IS
IP-classificatie	IP67

Regelgeving

Certificering	EN54-11
---------------	---------

Regulatory

BASIEFA	BAS02ATEX1290
Classification	E Ex ia IIc T5



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 18 February 2025 - 11:37