

TESTIFIRE-XTR2-HEAD

All-in-one connected smoke/heat detector test head

Powerful insights, automated test reports & records

The Testifire-XTR2 combines testing and reporting to deliver on compliance, giving service companies and building owners the insight and assurance they demand. The Testifire-XTR2 is designed to work with all detector brands and models, and with both addressable and conventional systems.

Test modes

The Testifire-XTR2 supports all-in-one smoke and heat testing including smoke only, heat or hi-heat only, combined and sequential smoke/heat as well as ASD test compatibility.

DT Connect App

Every Testifire-XTR2 includes a 6-month trial of DT Connect premium. When the 6-month trial period ends, a DT Connect subscription is needed to continue accessing the full range of features. The Testifire-XTR2 can also be used without subscription, albeit with limited features.

DT Connect alongside the Testifire-XTR2, allows advanced features to streamline the testing process, easily manage site assets and optimise reporting capability by automatically generating test reports.

DT Connect allows for:

- Minimising time spent on basic tasks
- Panel time logging to synchronise test and panel event timestamps *
- Test result capturing
- Asset identification *
- Panel reconciliation *
- Job summary
- Shareable reports *

* Premium DT Connect features

Product information

The Testifire-XTR2 head includes:

- 1 x TESTIFIRE-XTR2-HEAD
- 1 x TESTIFIRE-MEM Membrane 90 mm dia



Details

- Rapid smoke generation saves waiting time
- 50% faster heat and hi-heat activation compared with the legacy TM010
- Sequential & combined test modes including hi-heat testing up to 100°C
- TFT-LCD full colour touch screen user interface
- Automatic LED torch in dark environments
- Automatic test result capture with detector LED recognition support
- Clearing mode to prevent re-alarms
- Robust and repairable
- Bluetooth enables communication to the DT Connect App with 6-month free PREMIUM support
- Optional subscription for premium features in the DT Connect app and Cloud Portal

TESTIFIRE-XTR2-HEAD

All-in-one connected smoke/heat detector test head

Technische specificaties

Elektrisch

Type voeding	Batterijen
Bedrijfsspanning	10.8 V (35.1 wh / 3250 mAh)
Stroomverbruik	< 0.5 A rms (smoke testing) 4 to 6 A rms (heat testing)

Fysiek

Fysieke afmetingen	406 x 156 x 150 mm
Netto gewicht	1.25 kg
Verzendgewicht	2.39 kg
Kleur	Zwart, Grijs

Omgeving

Vandalbestendig	Nee
Bedrijfstemperatuur	5 to 45°C (41 to 113°F) - Head unit 5 to 40°C (41 to 104°F) - Charger cradle
Opslagtemperatuur	-10 to 50°C (14 to 122°F)
Relatieve vochtigheid	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Regelgeving

Conformiteit	CE, REACH, RoHS 3, WEEE
Certificering	CE

SKU info

Product brand	testifire
---------------	-----------

Test

Carbon Monoxide	No
Heat	Yes
Smoke	Yes

Electrical

Battery type	Lithium Ion
Charging	USB-C connection to charging cradle

Physical

Stimulus type	Cartridge
---------------	-----------

Compatibele producten

Categorie	Referentie	Beschrijving
Testapparatuur	CB001	Draagtas voor brand teststokken met toebehoren, etc
Testapparatuur	ET010	Telescopische teststok gemaakt van glasvezel. Lengte uitgeschoven 4,5 mtr
Testapparatuur	TES3-6PACK	
Testapparatuur	TESTIFIRE-ADAP	
Testapparatuur	TESTIFIRE-BP	
Testapparatuur	TESTIFIRE-CHAK	
Testapparatuur	TESTIFIRE-GEN-1PK	
Testapparatuur	TESTIFIRE-MEM	
Testapparatuur	TESTIFIRE-MEML	
Testapparatuur	TESTIFIRE-SOP	

Compatibele producten

Categorie	Referentie	Beschrijving
Testapparatuur	TESTIFIRE-XTR2	
Testapparatuur	TESTIFIRE-XTR2-6M	



Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 25 October 2024 - 13:14