

DM970

Apollo XP95 Series Intrinsically Safe MCP - Red Without Flap (55000-940)

General

The DM970 is an intrinsically safe manual call point. It should be used together with the PT971/2 protocol translator and GBX70 barrier. It is based on a standard weatherproof manual call point and features an "interrupt" facility to provide fast response to an alarm.

Application

When activated, the intrinsically safe call point interrupts the polling cycle to indicate to the control panel that it has been operated. Because of this feature, an alarm can be reported in less than 0.2 seconds.

The DM970 has the same operating characteristics as the standard manual call point versions. It is a red, break-glass call point to which a protective lift-up flap may be added as an option.



Detailjer

- Easy to install
- May be used with break glass or resettable element
- Easy to replace glass
- High quality micro switch
- Back box included
- IP67 rated
- BASEEFA certified

DM970

Apollo XP95 Series Intrinsically Safe MCP - Red Without Flap (55000-940)

Tekniska specifikationer

Allmänt

Statusindikering	Red Alarm LED
------------------	---------------

Elektrisk

Driftspänning	14 to 22 VDC
Nuvarande förbrukning	230 µA (Quiescent) 4 mA (Alarm)

Fysisk

Fysiska dimensioner	124 x 124 x 60 mm
Nettovikt	± 400 g
Färg	Röd

Miljö

Driftstemperatur	-20 to +40°C (T5) / -20 to +60°C (T4)
Lagringstemperatur	-30 to +80°C
Relativ luftfuktighet	0 to 95% noncondensing
Miljö	Inomhus, IS
IP-betyg	IP67

Reglerande

Intygande	EN54-11
-----------	---------

Regulatory

BASIEFA	BAS02ATEX1290
Classification	E Ex ia IIc T5



Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 18 February 2025 - 11:37