

FF756

UV/dubbel IR flamdetektor i flamsäker kapsling (IP66) med reläer.

General

The FF756 is a UV / IR² flame detector in a flame proof housing. UV / IR² models have excellent response to flame while providing immunity to extraneous sources. New micro-processor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapor. A high and low sensitivity setting according to EN54-10 is provided.

Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR² unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.

Reducing false alarms

Most IR flame sensors respond to 4.3µm light, emitted by hydrocarbon flames. By responding to 1.0 to 2.7µm light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The combination of UV and IR² detection, plus signal processing allows the UV / IR² sensor to be used without risk of false alarms in difficult situations characterised factors such as flickering blackbody radiation or arc welding.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.



Detaljer

- UV/Dual IR detector
- High specification units for critical applications
- IP66 Housing
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- Conforms to EN54: Part 10

FF756

UV/dubbel IR flamdetektor i flamsäker kapsling (IP66) med reläer.

Tekniska specifikationer

Elektrisk

Driftspänning	14 to 28 VDC
---------------	--------------

Fysisk

Nettovikt	2.5 kg
-----------	--------

Monteringstyp	Ytmontering
---------------	-------------

Miljö

Driftstemperatur	-10 to +55°C
------------------	--------------

Lagringstemperatur	-20 to +65°C
--------------------	--------------

Relativ luftfuktighet	95% max. noncondensing
-----------------------	------------------------

Miljö	Exd, Inomhus, Utomhus
-------	-----------------------

IP-betyg	IP66
----------	------

Supply voltage

14 - 28 V dc

Supply current

3/9, 4/8/14, 4-20, 8-20 mA

Relay contact ratings

1 A @ 30 V dc (resistive load)

Field of view

90° min. cone

Spectral response (IR)

1.0 to 2 µm

Spectral response (UV)

185 to 260 nm

Operating temperature

-10°C to 55°C

Storage temperature

-20°C to 65°C

Relative humidity

95%; non-condensing

IP Rating

IP66

Weight

2.5 kg

IEC marking

EEx d IIC T6

Kompatibla produkter

Kategori	Referens	Beskrivning
Detektorer	FF705	Justerbar monteringskonsol.



Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 18 February 2025 - 11:37