

# AIO

ALL-IN-ONE DETECTORS



**KIDDE**  
COMMERCIAL



**Catching the First Heartbeat**



**Emerging From Silence**

**KIDDE**  
COMMERCIAL

**NEW EXCELLENCE SERIES DETECTORS  
WITH NOTIFICATION**

All-inclusive solution for a  
variety of applications



**EN54-APPROVED VARIANTS  
WITH INTEGRATED  
ISOLATION, SOUNDER  
AND VAD**

This range eliminates the  
need for separate sounders  
and VADs, saving both  
installation time and costs



# INSTALLATION FEATURES



- Easy alignment of detector and base
- Secure connection of detector with base with multiple contact locations
- DUAL Status indication always visible (360° visibility)
- Clear (and subtle) device type marking on every device
- Easy labelling, tag matching to base
- Detector lock, preventing unauthorised removal
- QR code, for quick information retrieval
- Easy traceability with laser marking
- Easy addressing and verification

# THE RANGE

## TRAFFIC WHITE

- Dual optical with smoke discrimination & sounder
- Dual optical with smoke discrimination & sounder/VAD
- Multisensor, dual optical with smoke discrimination, heat (class-A, static or rate-of-rise) & sounder
- Multisensor, dual optical with smoke discrimination, heat (class-A, static or rate-of-rise) & sounder/VAD



## GRAPHITE BLACK

- Multisensor, dual optical with smoke discrimination, heat (class-A static or rate-of-rise) & sounder/VAD

The image features a dark, monochromatic background with silhouettes of office workers in various poses: sitting at a desk, standing, and walking. A prominent red heartbeat line runs horizontally across the center, with a glowing orange-red glow around it. The overall aesthetic is professional and modern.

**A FULL SPECTRUM  
OF INSTALLATION POSSIBILITIES**

**CLEAR & STYLISH INDICATION,  
ADDED SAFETY & EASIER MAINTENANCE**

# CONVENIENCE

# AESTHETICS & SAFETY



**Address label location  
for easy labelling / matching to the base label**

**Hidden sounder  
& thermistors**







# THE USER INTERFACE

Commonality for all variants



NOTIFICATION LEDs

DUAL TRI-COLOUR NOTIFICATION USING LEDs FOR CLEAR VISIBILITY

Flashing <b>GREEN</b>		Communications (optional)
Steady <b>GREEN</b>		Location / Power up
Flashing <b>YELLOW</b>		Fault
Constant <b>YELLOW</b>		Isolated
Flashing <b>RED</b>		Pre-alarm
Constant <b>RED</b>		Alarm



## NOTIFICATION OPTIONS

### **AUDIBLE**

- 32 freely configurable tones
- 4 freely configurable SPL levels from 51 to 86 dBA

### **VISUAL**

- 3 freely configurable power levels:
- Low (O-2.5-7)
  - Standard (C-3-7.5)
  - High (C-3-9)



**KIDDE**  
**COMMERCIAL**

**BUILDING A SAFER  
TOMORROW ...  
TODAY**

**Find us**

[www.FireSecurityProducts.com](http://www.FireSecurityProducts.com)

[in](#) Kidde Commercial - EMEA