

## **DECLARATION OF PERFORMANCE** (in accordance with the Construction Products Regulation)

**No. UTCAPDL1CPR2015-07-15**

1. Unique identification code of the product type:

**UTC Digital Location Control Unit (ADLCU)**  
**(for use with Digital Linear Heat Detection Cables)**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**See product label on inside of product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Alarm point distance locator for location of alarm point**  
**for use with non-resettable line-type heat detector**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Thermocable Flexible Elements Ltd**  
**Pasture Lane**  
**Clayton, Bradford**  
**BD14 6LU**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**FM Approval Standard - Heat Detectors for Automatic Fire Signaling - Class 3210 April 2007.**  
**Low Voltage Directive (LVD) 2006/95/EC**  
**Restriction of the Use of Certain Hazardous Substances (RoHS) in Electrical and Electronic**  
**Equipment (EEE) Directive (2011/65/EU)**

Pasture Lane Clayton Bradford West Yorkshire  
BD14 6LU England United Kingdom  
Tel: +44(0)1274 882359 • Fax: +44(0)1274 882229  
E-mail: info@thermocable.com

---

8.Declared Performance:

<b>Operating Voltage Range</b>	9 – 28V DC
<b>Ambient temperature operating range</b>	0°C – 49°C (32°F – 120°F)
<b>Current Consumption</b>	0.09A max (with LCD backlight on)
<b>IP Rating</b>	IP65/IK08 rated polycarbonate with hinged removable cover and hinged removable internal front plate
<b>Dimensions</b>	W180mm x H130mm x D78mm (W7" x H5 1/8" x D3")

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.


**Signed for and on behalf of the manufacturer by:**

**Philip Wilkie – Technical Director**

.....  
(name and function)

Thermocable Flexible Elements Ltd  
on 15<sup>th</sup> July 2015

.....  
(placed and date of issue)



.....  
(signature)