

TruVision DVR 12HD/44HD Firmware 1.2h Release Notes

P/N 1073280A • REV A • ISS 12JAN17

Introduction

This is the TruVision DVR 12HD/44HD Firmware 1.2h Release Notes document with additional information not covered in the user manual. For the latest information on the recorders, please visit:

Americas: <http://www.interlogix.com/videoupgrades>

EMEA: www.utcssecurityproducts.eu

Australia: www.interlogix.com.au

Overview

The TruVision DVR 12HD/12 cHD (TVR 12HD/12cHD) and DVR 44HD (TVR 44HD) are HD Hybrid video recorders capable of recording up to 4 (TVR 12HD only), 8 or 16 camera inputs.

This HD Hybrid recorder brings us a unique product to the market that is uniquely qualified to upgrade existing analog installations, offering a competitive and practical solution for the market of HD analog, standard analog and hybrid recorders.

Summary of new features and key enhancements

- The standard setting for PTZ control has been set to TruVision-Coax instead of Interlogix-485
- The standard setting for the RS-232 port has been set to Technical support instead of ProBridge.

Contacting support

For help installing, operating, maintaining, and troubleshooting this product, refer to this document and any other documentation provided. If you still have questions, contact us during business hours (Monday through Friday, excluding holidays).

Note: Please be ready at the equipment before calling.

Table 1: Technical support

North America

T +1 855.286.8889

E techsupport@interlogix.com

W www.interlogix.com/customer-support

Europe, Middle East, and Africa

W Select *Contact Us* at www.utcssecurityproducts.eu

Australia

E security.tech.support@interlogix.com.au
