

6540

PIR detektor m. fresnel objektiv 12m med indbygget 3K3 EOL modstand

DesignLine Series-PIR Technology

The DesignLine series is a range of motion sensor using a PIR element and digital signal processing.

This series is suitable for residential and light commercial environments.

The DesignLine series builds customer value by meeting customers' security needs while respecting budget constraints. This range is quick to install and comes with a stylish housing.

It provides detection for a variety of ranges, including up to 360 degrees of coverage for ceiling mount applications. It even has a variant with smart pet immunity up to 35kg, making this series all the more attractive.

These motion sensors deliver easy solutions for installers - being equipped with a standard EOL resistor and providing flexibility in installing height and are the ideal security solution for residential and light commercial applications.

Accessories

A wall and ceiling mount bracket (6545-BP) is available providing ease-of-use to the installer and flexibility to aim the detector where required.

The Fresnel lens of the 6540 can be taken out and replaced by a curtain lens (6545-CL) or a long-range lens (6545-LR).



Detaljer

- Passive Infra Red motion sensor
- Digital signal processing
- Unique stylish design
- Quick to install
- Built-in EOL resistor of 3k3 Ohm
- EN50131 Grade 2
- Holds several European security approvals

6540

PIR detektor m. fresnel objektiv 12m med indbygget 3K3 EOL modstand

Tekniske specifikationer

Generelt

Teknologi	PIR
Applikationstype	Vægmontering
Anti maskering	Nej
Kæledyrs immunitet	Nej
Kamera	Nej

Detektering

Maks. detektionsområde	12 m
Underbeskyttelse	Nej
Målhastighedsområde	0.3 to 3.0 m/s

Wired / trådløs

Wired / trådløs	Kablede
-----------------	---------

Indgange / udgange

Alarmrelæ karakteristik	NC, 50 mA, < 24 VDC
Sabotage relæ karakteristik	NC, 50 mA, < 24 VDC
Relæ konfiguration	3k3 EOL

Elektrisk

Driftsspænding	9 to 15 VDC
Nuværende forbrug	8.7 mA

Fysisk

Fysiske dimensioner	123 x 66 x 42 mm
Nettovægt	94 g
Farve	Hvid
Monteringshøjde	1.5 to 3.1 m

Miljø

Driftstemperatur	-10 to 55 °C
Relativ luftfugtighed	max. 95%
Miljø	Indendør

RegulerendeRegulativ

EN50131 kvalitet	Lønklasse 2
------------------	-------------



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 5 May 2023 - 10:27