ACL800SUW-RDPX-S

ACL800 EM/CASI/HID Prox læser - Wiegand, HID Pass-Through, Overflade monteret, Sølv

Product description

These surface mount proximity readers includes a buzzer and a tri-color LED for state indication (access granted, access denied or idle). ACL800SUW-RDPX is capable of reading Casi Rusco, EM and HID compatible cards/fobs (125 kHz).

The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.

Card technology

The readers are compatible with the TruPortal (125 KHz) credential range. The Proximity card type can be selected through DIP switches in "HID only", "HID and EM", "HID and Casi", "Casi only" or "EM only" and Wiegand outputs automatically according to the card type.

Compatibility

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.

Detaljer

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Compatible with the TruPortal learn-in reader (TP-RDR-LRN)
- Backlight illumination
- 125 KHz EM/CASI/HID Proximity reader

ACL800SUW-RDPX-S

ACL800 EM/CASI/HID Prox læser - Wiegand, HID Pass-Through, Overflade monteret, Sølv

Tekniske specifikationer

System

Maks. læser afstand til panel	50 m
CSN (kortets serienummer)	Ja
Antal lysdioder	3
Sproginstallationsmanual	English

Teknologi

Læsertype	Nærhed
Readerens driftssendende frekvens	125 KHz
Understøttet teknologi 125 kHz	EM4102, GE ProxLite/CASI Prox, HID Prox

Interface & forbindelser

Grænseflade	Wiegand
Tilslutningstype	Svinesvans
Pigtail længde	100 cm

Manipulation type

Pry-off tamper	Nej
Åbningspjæld	Ja

Operation

Autonom	Nej
PIN-tastatur	Nej
Green LED	Potential Free
Red LED	Potential Free
Orange LED	Idle mode
Illumination	Blue backlight (programmable on/off control)
Buzzer	1 (internal)

Elektrisk

Strømforsyningstype	VDC
Strømforsyningsværdi	9 to 14 VDC
Nuværende forbrug	100 mA at 24 VDC

Fysisk

Fysiske dimensioner	92 x 52 x 27 mm
Nettovægt	300 g
Forsendelsesvægt	310 g
Farve	Sølv
Materiale	Støbt aluminium
Form faktor	Mullion
Monteringstype	Overflademontering

Miljø

Miljø	Indendør, Udendørs
Stuetemperatur	-20 to +50°C
Relativ luftfugtighed	5 to 93% noncondensing

Regulerende

Overholdelse	CE, RoHS

Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 6 September 2023 - 12:20