

# DC143

**Magnetkontakt til påbygning. Afstand  $\pm$  9-31 mm, NC.**

## Industrial Surface Mount Contact

---

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

## Applications

---

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.



## Detaljer

---

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

# DC143

Magnetkontakt til påbygning. Afstand  $\pm 9-31$  mm, NC.

## Tekniske specifikationer

---

### Generelt

Applikationstype	Overflademontering
Kontakt type	CO
Forbindelse	Screw

### Wired / trådløs

Wired / trådløs	Kablede
Driftsgab	9 mm (min.); 31 mm (max.)

### Fysisk

Fysiske dimensioner	99 x 17 x 15 mm
Farve	Beige



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på [dk.firesecurityproducts.com](http://dk.firesecurityproducts.com) eller ved at kontakte din salgsrepræsentant hos.

Last updated on 5 May 2023 - 9:33