

SMA-LP-MULTI

MA SIGMA Lite Plus - Multi, 2.8 inch QVGA touchscreen, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, IP65, 500 users, CE

MA SIGMA Lite & MA SIGMA Lite Plus Series

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door Mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

Embedded web server

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tablet, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

Enhanced interactivity

Thanks to the 2.8" QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

Compatible with existing installations

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioScript network.

Enhanced security features

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.



Detaljer

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, ICLASS or MIFARE/DESFire contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

SMA-LP-MULTI

MA SIGMA Lite Plus - Multi, 2.8 inch QVGA touchscreen, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFire, IP65, 500 users, CE

Tekniske specifikationer

System

Læseafstand	1.5 cm
Maks. læser afstand til panel	Ethernet: 100 m, RS485: 1219 m
RTE (anmodning om udgang)	Nej
CSN (kortets serienummer)	Ja
Tilpasset datamodel	Ja
Antal lysdioder	1

Teknologi

Læsertype	BioMetric
Readerens driftssendende frekvens	13.56 MHz
Understøttet teknologi 13,56 MHz	MIFARE Classic (CSN), MIFARE Classic (custom data), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Plus (CSN, level 1 and 3), NFC (CSN)
SAM-modul indlejret	Nej

Biometrisk

Biometrisk type	Fingerprint
Biometrisk sensortype	Optical

Interface & forbindelser

Grænseflade	Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand
Tilslutningstype	Netværk, Svinesvans
Pigtail længde	30 cm

Manipulation type

Pry-off tamper	Nej
Åbningspjæld	Ja

Operation

Autonom	Ja
PIN-tastatur	Ja
PIN-længde	6

Elektrisk

Strømforsyningstype	PoE ind
Strømforsyningsværdi	12 to 24 VDC

Fysisk

Fysiske dimensioner	68 x 156 x 62 mm
Nettovægt	280 g
Forsendelsesvægt	325 g
Farve	Sort
Materiale	Polycarbonat
Form faktor	Overdimensioneret
Monteringstype	Overflademontering

Miljø

Vandalt bevis	Nej
Miljø	Udendørs
Driftstemperatur	-20 to +55°C
Stuetemperatur	-20 to +55°C
Relativ luftfugtighed	10 to 80% noncondensing
IP-vurdering	IP 65

Regulerende

Overholdelse	CE, FCC, ICASA, REACH, RoHS, UL 294, WEEE
--------------	---

