

TVB-2402

TruVision™ Analog Bullet kamera, HD-TVI, 720p, 2.8-12 mm.

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Detaljer

- 720p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 40 m
- IP66 environmental rating
- Digital wide dynamic range
- 2.8 to 12 mm lens
- Dual power 12 VDC / 24 VAC
- Bracket included
- Provide OSD control via TruVision up the coax and built-in menu button

TVB-2402

TruVision™ Analog Bullet kamera, HD-TVI, 720p, 2.8-12 mm.

Tekniske specifikationer

Generelt

Teknologi	HD-TVI-analog
Videostandard	PAL

Kamera

Sensorstørrelse	1/3"
Maks. løsnings	720p
Sensorscanning	Progressive
Sensortype	CMOS
Totalt antall piksler (H x V)	1305 x 1049
Effektive pixels (H x V)	1305 x 1049
Digital S/N-forhold	More than 62 dB
Lukketid	1/25 to 1/50,000 s

Belysningsdydeevne

WDR-type	Digital WDR
Digital støjreduktion	3D DNR
Dag nat	True Day/Night
Motoriseret IR-skåret filter	Ja
Farvesensitivitet	0.01 Lux @ (F1.2, AGC ON), 0.014 Lux @
S / H-følsomhed	0 Lux with IR on
Infrarød (IR)	Ja
IR-rækkevidde	40m

Linse

Objektivtype	Varifokal
Brændvidde	2.8 - 12 mm @ F1.4

Netværk

Integration	CGI, ONVIF, PSIA
-------------	------------------

Elektrisk

Driftsspænding	12 VDC / 24 VAC
Strømforbrug	12 VDC: max. 4 W / 24 VAC: max. 6W
Nuværende forbrug	12 VDC: max. 0.33A / 24 VAC: max. 0.25A

Fysisk

Fysiske dimensioner	105 x 94.7 x 301.4mm (4.13 x 3.74 x 11.86 in.)
Nettovægt	1075 g
Farve	Grå
Form Factor	Kugle

Miljø

Miljø	Udendørs
Driftstemperatur	-30 to +60 °C (-22 to +140 °F)
Stuetemperatur	-20 to +70° C (-4 to +158° F)
IP-vurdering	IP66

Regulerende

Overholdelse	C-tick, CE, FCC, REACH, RoHS, UL, WEEE
--------------	--

Kamera

Sync. system	Internal
Video output	Dual HD-TVI or 960H
OSD	Built-in OSD button, TruVision Coax OSD control on both HD-TVI and 960H



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 24 January 2024 - 16:10