TVF-1106

TruVision 360 Degree IP Dome, 3.0 MPX, PAL, WDR, Outdoor, 1.19mm fisheye lens, true D/N, 10m IR, 2 way audio (built-in mic & speaker), SD/SHDC slot, PoE (803.af) /12VDC,IP66, IK10,

Overview

Ideally suited for a variety of applications including retail, commercial, law enforcement and education environments, the TruVision 360º network dome camera provides high-quality image capture, that delivers a complete view of indoor or outdoor areas for exceptional security coverage. Supporting 3MPx sensors, these cameras are PoE 802.3af powered making installation as easy as running a Category 5e cable to the camera location. Particularly effective in areas where a wide area needs to be covered, such as intersecting corridors, parking garages, counters and warehouses. The 360º camera can also be used in a wall-mount configuration to capture panoramic scenes. With an IR range of up to 10m, they can also be used in low-light environments and for 24/7 exterior surveillance. Extra mounting accessories are available for pendant mount and wall mount installation. The cameras can be used with our TruVision NVRs and Prism

Detaljer

- 3MPx 1/3" progressive scan CMOS
- Up to 2048 x 1536 real-time streaming
- 360° view angle
- Multiple viewing modes
- Multiple ePTZ streams with preset and patrol functions
- Up to 10m IR range
- 2-way audio, built-in mic and speaker
- Built-in SD/SDHC card slot
- Ceiling, wall and desk mount options
- Outdoor version
- Operating temperature range -30 to 60°C

TVF-1106

TruVision 360 Degree IP Dome, 3.0 MPX, PAL, WDR, Outdoor, 1.19mm fisheye lens, true D/N, 10m IR, 2 way audio (built-in mic & speaker), SD/SHDC slot, PoE (803.af) /12VDC,IP66, IK10,

Tekniske specifikationer

Generelt

Teknologi	IP
Videostandard	PAL

Kamera

Sensorstørrelse	1/3"
Maks. løsning	3 MP
Sensorscanning	Progressive
Sensortype	CMOS
Totalt antall piksler (H x V)	2048 x 1536
Digital S/N-forhold	50 dB
Lukketid	1/25 to 1/100.000s

Belysningsydeevne

WDR	120 dB
Digital støjreduktion	3D DNR
Dag nat	True Day/Night
Motoriseret IR-skåret filter	Ja
Farvesensitivitet	0.28lux @(F2.0, AGC ON)
S / H-følsomhed	0 lux with IR
Infrarød (IR)	Ja
IR-rækkevidde	10 m
IR-bølgelængde	850 nm

Indkodning

Hovedstrømskomprimering	H.264
Maks. opløsning @ fps	2048 x 1536 @25 fps
Understøttelse af høj frame mode	50Hz: 1 x fisheye (2048 x 1536, 25fps) or (1536 x 1536, 25fps) or 4 x PTZ (800 x 600, 25fps)

Linse

Objektivtype	Fast
Brændvidde	1.19 mm
f-stop	1.4

Netværk

Integration	CGI, ONVIF, PSIA

Audio

Lydkomprimering	AAC, G.711, G.726
Lyd ind	Internal Microphone
Audio ud	Internal Speaker

Opbevaring

Understøttelse af lokal opbevaring	Ja
Lokal opbevaringstype	Built-in SD/SDHC Slot
Max. SD card capacity	64 GB

Video-intelligens

Alarmtrigger	Motion detection, Video tampering

Elektrisk

Driftsspænding	12 VDC
Strømforsyningstype	PoE ind
Strømforbrug	12 W max.
Nuværende forbrug	1 A

Fysisk

Fysiske dimensioner	167 x 45 mm
Nettovægt	767 g
Farve	Hvid
Form Factor	360 grader

Miljø

Effektvurdering	IK10
Miljø	Udendørs
Driftstemperatur	-30 to +60°C -22 to +140°F
IP-vurdering	IP66

Regulerende

Overholdelse	C-tick, CE, FCC, REACH, RoHS, UL, WEEE

Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 5 May 2023 - 9:37