

# TVK-600

## TruVision RS485/IP tastatur, 4-aksel joystick, 12VDC

### Overview

The TVK-600 keypad has been designed to be used with the line of TruVision NVRs, DVRs, PTZ cameras, encoders and decoders. A TVK-600 lets you easily control the monitor outputs of a recorder and a decoder, allows precise PTZ control, and gives you full control of every recorder's user interface using only the keypad.

### Full featured

The TVK-600 contains all features to control a TruVision device efficiently.

The keypad can communicate via IP or RS485 with supported recorders and cameras.

The configuration of the keypad is done via a web browser.

Different user modes can be selected via the on-screen menu of the LCD display.

The keypad supports up to 1000 devices via keyboard mode.

Users can navigate through the menu of a recorder and control PTZ cameras via the 4-axis joystick.

### Why TVK-600?

The TVK-600 lets you control your video system via one user interface without using a PC.

### Applications

The TVK-600 is ideal for guard rooms and monitoring centers.



### Detaljer

- Control a variety of NVRs, DVRs, decoders, PTZ cameras with one keypad
- Communication via IP or RS485
- 4-axis joystick
- Numeric and functional buttons
- Supports PTZ control (analog and IP)
- Control monitor outputs of recorders
- Supports up to 1000 devices via keyboard mode
- Configuration and device management via webpage
- Control the recorder OSD
- Set and call presets and preset tours of PTZ cameras

# TVK-600

TruVision RS485/IP tastatur, 4-aksel joystick, 12VDC

## Tekniske specifikationer

### Generelt

Tastatur / controller type Analog / seriel, IP

### Kontrol

Joystick-type 4-akse

Knapper Numeric and functional

### Brugergrænseflade

Skærmtypen 128x64 pixel screen

### Grænseflader

Forbindelsesgrænseflade Ethernet, RS-485

### Elektrisk

Strømforsyningstype 12 VDC

Strømforsyningssværdi 12 V

Strømforbrug <= 4.5 W

### Fysisk

Fysiske dimensioner 435 x 193 x 110 mm

Nettovægt 1 kg

Farve Sort

### Miljø

Driftstemperatur -10 to +55°C

Relativ luftfugtighed 10 to 90%

### Regulerende

Overholdelse CE, RoHS, WEEE

### Interfaces

Network interface 10 / 100 Mbps self-adaptive Ethernet interface

USB USB 2.0

### Supported products

#### Devices

TruVision PTZ cameras:

TruVision S1 PTZ cameras (TVP-310x / 110x / 3122 / 1122)

TruVision IP Compact PTZ cameras

TruVision IP Full Size PTZ cameras

TruVision Stainless Steel IP PTZ cameras

TruVision TVI PTZ cameras

TruVision recorders:

TVN 11 series

TVN 21 series

TVN 22 series

TVR 15HD series

TVR 45HD series

TVR 46 series

TVR 40 series

TVR 41 series

TVR 42 series

TVR 60 series

TruVision decoders:

TVE-DEC11

TVE-DEC12

TruVision encoders and non-PTZ IP cameras:  
only as input.

See configuration manual (Appendix A) for more  
detailed information.



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktsspecifikationer uden varsel. De nyeste produktsspecifikationer kan du finde på [dk.firesecurityproducts.com](http://dk.firesecurityproducts.com) eller ved at kontakte din salgsrepræsentant hos.