



TVN-1108-KB2

TVN 11 kit, 8 kanals NVR m/4 2MPx (4 mm) IR Bullet kameraer



Detaljer

- Linux embedded recorder with Plug and Play configuration
- Recorder and cameras support H.264 and H.265
- Eight Plug & Play PoE ports (PoE-af & PoE-at support) with flexible budgeting
- Automatic setup of IP address, resolution & other settings through Plug&Play ports of the recorder
- Up to 80 Mbps camera recording bandwidth for maximum eight IP cameras
- Recorder with 2 TB embedded storage
- Real time Full HD recording
- Motion detection, VCA, privacy masking and tamper detection in recorder
- TruVision IP camera auto-detection
- Integration in recorder of Carrier IP intrusion panels via SIA/XSIA reporting
- Full browser-, OSD-, and software-based access for live, recorded video & configuration
- Bullet camera with a maximum resolution of 1920 x 1080
- Cameras: H.265 and/or H.264 compression with triple-streaming functionality
- Edge recording up to 128 GB SDHC in cameras
- Up to 30 m IR illumination
- Up to 120 dB Wide Dynamic Range
- Video intelligence in cameras: face detection, intrusion detection cross line detection
- TVRMobile app for iOS and Android
- TruVision Navigator license-free client/host or standalone application

- External integration through SDK

Overview

The TVN-1108-KB2 is a 4-channel video kit, that consists of one 8-channel network recorder (TVN-1108S-2T) and four 2 MPx (4 mm) bullet cameras.

The recorder has eight built-in PoE ports for ease of installation.

For more information about the recorder and cameras, see the individual datasheets.

TVN-1108-KB2

TVN 11 kit, 8 kanals NVR m/4 2MPx (4 mm) IR Bullet kameraer

Tekniske specifikationer

Generelt

Teknologi	IP
Operativ system	Embedded Linux
Kan monteres på stativ	Ja
Rackstørrelse	1 U

Video / audio input

Kamerakanaler	8
Edge failover-optagelse	8
Kameraets båndbredde	80
Maks. IP-lyd ind	8
Max. analoge audio-in	1
Understøttede videokomprimeringsstandarder	H.264, H.265
Understøttede standarder for videostreaming	Onvif, RTSP

Lokal visning

HDMI-udgang	1
HDMI-version	1.4, 2.0
VGA-udgang	1
Maks. lokal outputopløsning	Full HD 1080p
OSD for synkron afspilning (kanaler)	Up to 4 channels (1080P)
Omvendt afspilning OSD (kanaler)	Up to 1 channel

Fjernvisning

Total tilgængelig båndbredde	80
Maks. livestreams	128 streams
Maks. afspilning af streams	8 streams
Maks. samtidig afspilning webbrowser	TCP: Up to 16 ch; UDP: Up to 8 ch
Omvendt afspilningswebbrowser (kanaler)	TCP: Up to 16 ch; UDP: Up to 8 ch
Softwarekompatibilitet	Advisor Management Software (ATS8600), OnGuard, TruVision Navigator, TVRmobile
Browser kompatibilitet	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Opbevaring

Opbevaringskapacitet	2 TB
Maksimal optagelsesopløsning	4 K
Optagelsestilstande	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Harddiskredundans	Nej
Harddiskgruppering	Nej
Hot-swap-harddiske	Nej
SAS udvidelse	Nej
Flip-open frontpanel	Nej
Automatisk arkivering	Nej
Hot reserveoptager	Nej
Edge failover-optagelse	Nej

Netværk

Netværksinterfacekort (NIC)	1
NIC-type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE ports	8
Totalt PoE-budsjett	120
PoE-standarder understøttet	PoE-af, PoE-at
Maks. PoE-budget pr. Port	30
Plug & Play PoE-understøttelse	Ja
Fleksibel PoE-tildeling	Ja
DNS-support	DDNS, ezDDNS, Ingen IP
HTTPS support	Ja

Ekstern interface

USB-grensesnitt tilbage	1
USB-grensesnitt foran	1
Alarmindgange	4
Alarmuitgangen	1
Maks. analoge lydudgange	1

Elektrisk

Driftsspænding	100 to 240 VAC
Strømforbrug uden HDD (W)	180

Fysisk

Fysiske dimensioner	380 x 320 x 48 mm
Nettovægt	2.4 kg
Farve	Sort

Miljø

Driftstemperatur	-10 to +55 °C
Relativ luftfugtighed	10 to 90% noncondensing

TVN-1108-KB2

TVN 11 kit, 8 kanals NVR m/4 2MPx (4 mm) IR Bullet kameraer

Regulerende

Overholdelse	CE, REACH, RoHS, UL
--------------	---------------------



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 9 March 2023 - 16:10