

TVN-7101-32T

TruVision NVR 71, Netværks videooptager, 576 Mbps/128 kanaler H.265 NVR, 32TB, NON-RAID

Overview

TruVision NVR 71 (TVN 71) is a high quality reliable embedded network video recorder. The device is able to manage up to 576 Mbps of incoming camera bandwidth, or up to 128 camera channels. The amount of incoming bandwidth will define how many cameras that can be connected.

To accommodate for these vast amounts of data, TVN 71 can be equipped with up to 96 TB of embedded storage in a non-RAID or a RAID configuration. Please note that different models of TVN 71 are available for non-RAID and RAID configurations. A non-RAID model can't be used in a RAID configuration!

Performance made accessible

TVN 71 offers higher end performance without the requirement of high end configuration. Functionality such as RAID (only with specific models!), advanced camera settings, fail-over recording, hard drive grouping, network segregation or network redundancy can be set up efficiently and easily, without the need of any advanced product training.

TVN 71 uses a similar familiar user interface as all other TruVision recorders, and can be operated by the same sets of software and apps as the whole TruVision portfolio, limiting training requirements drastically for technicians, operators and other users of the system.

H.265

The TVN 71 is supporting both H.264 and H.265 compression techniques. The H.265 compression is the next evolution of video encoding. Using H.265 will result in a reduced file size for the same video content and a reduced transmission bandwidth compared to H.264. This means that for the same storage capacity more video can be stored when using H.265 than H.264 encoding.

To use the H.265 encoding in the TVN 71, TruVision H.265 cameras need to be used.

Intrusion integration

TVN 71 has an alarm receiver module embedded inside. The alarm message receiver can connect to up to three Interlogix IP intrusion panels that report in SIA or XSIA format. Alarm messages, disarming and arming messages can be sent from the alarm panel to the recorder, which then can take actions (trigger alarm recording, send a PTZ to a preset, run a shadow tour or preset tour, trigger an alarm output, send an email, send a notification message to TVRMobile or to TruVision Navigator (as of version 7.1)).

Also the heartbeat message between panel and recorder is monitored. This solution offers straightforward alarm verification and is free of charge.

Broad redundancy options

In large scale systems it is important to limit single point of failure. For this reason, TVN 71 offers a large number of redundancy features,



Detaljer

- Linux embedded Plug and Play configuration
- Up to 576 Mbps camera recording bandwidth or max .128 cameras
- 32 TB non-RAID storage, expandable via hard drive kits (4 TB, 6 TB)
- Real-time Full HD recording
- Full browser-based access for live, recorded & configuration
- Motion detection, VCA, privacy masking, tamper detection
- Integration of Carrier IP intrusion panels via SIA/XSIA reporting
- TruVision IP camera auto-discovery
- Native TruVision IP camera support & broad third party camera support through ONVIF
- Customer protocol configuration (RTSP streaming)
- Flip-open front panel for easy HDD access, servicing & expansion
- Network redundancy (NIC, port, network)
- PSU redundancy
- Replaceable fan
- Recorder fail-over functionality (one fail-over unit per 4 operational recorders)
- TruVision Navigator license-free client/host or standalone application
- TVRMobile app for iOS and Android

including NIC redundancy, network port redundancy, PSU redundancy, Fail-over recording as well as Edge fail-over recording.

TVN-7101-32T

TruVision NVR 71, Netværks videooptager, 576 Mbps/128 kanaler H.265 NVR, 32TB, NON-RAID

Tekniske specifikationer

Generelt

Teknologi	IP
Operativ system	Embedded Linux
Kan monteres på stativ	Ja
Rackstørrelse	3 U
Aftagelig blæser	Ja
Redundant strømforsyning	Ja

Video / audio input

Kamerakanaler	128
Maks. båndbredde pr. kanal	16 Mbps
Kameraets båndbredde	576 Mbps
Maks. IP-lyd ind	128
Max. analoge audio-in	1
Understøttede videokomprimeringsstandarder	H.264, H.265
Understøttede standarder for videostreaming	Onvif, RTSP Custom Protocols

Fjernvisning

Total tilgængelig båndbredde	512 Mbps
Maks. livestreams	256
Maks. afspilning af streams	256
Maks. forbindelser til optager (ikke-visning)	256
Softwarekompatibilitet	Advisor Management Software (ATS8600), OnGuard, TruVision Navigator, TVRmobile
Browser kompatibilitet	Internet Explorer

Opbevaring

Opbevaringskapacitet	32 TB
SATA-grænseflader	16
Maks. kapacitet pr. HDD (TB)	6
Maksimal optagelsesopløsning	8 MP
Optagelsestilstande	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Dual stream-optagelse (kanaler)	128
Ekstern lagring	NAS
Harddiskredundans	Ja
Harddiskgruppering	Ja
Hot-swap-harddiske	Ja
Flip-open frontpanel	Ja
Automatisk arkivering	Ja
Hot reserveoptager	Ja
Edge failover-optagelse	Ja

Netværk

Netværksinterfacekort (NIC)	8 (4x RJ45; 4x SFP)
NIC-type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
NIC-tilstand	Load balancing, Multi-address Mode, Network Redundancy
Netværksporte pr. NIC	1
DNS-support	DDNS, ezDDNS, Ingen IP
HTTPS support	Ja

Ekstern interface

USB-grensesnitt tilbage	2
USB-grensesnitt foran	2
Seriell grænseflade	RS-232
Alarmindgange	16
Alarmuitgangen	8
Maks. analoge lydudgange	1

Elektrisk

Driftsspænding	100 - 240 VAC
----------------	---------------

Fysisk

Fysiske dimensioner	442 x 494 x 146 mm (W x D x H)
Farve	Sort

Miljø

Driftstemperatur	-10 to +55°C
Relativ luftfugtighed	10% to 90%

Regulerende

Overholdelse	CE, cUL, FCC, RCM, REACH, RoHS, UL, WEEE
--------------	--



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 26 August 2024 - 15:40