

# TVP-2401

## Bevægeligt HD-TVI kamera PTZ, med Zoom 30x optisk (16x digitalt).

### Overview

---

The TruVision HD-TVI Analog PTZ Cameras by Interlogix® utilize the latest PTZ technology to provide powerful, cost-effective surveillance for retail, commercial and small business applications. With 1080p resolution and a 30X optical zoom (16X digital) working together, these cameras deliver crisp, clear images, even at a distance.

With advanced features, such as True Day/Night surveillance and Digital Wide Dynamic Range (DWDR) imaging, these cameras provide optimal image quality in a variety of indoor or outdoor environments. HD-TVI Analog PTZ cameras are easy to change, with wall, pendant (IR or non IR), surface or flush mounting options to meet various application needs.

These cameras are also fully programmable, with up to 256 presets, 8 preset tours, and shadow tours for end-user customization and flexibility. A 24-zone privacy-mask feature allows these cameras to block out sensitive areas, such as fitting rooms, or restricted areas. Motion detection, privacy masking and electronic image stabilization add substantial value and enhanced security to any surveillance system.



### Detaljer

---

- 1/3" Progressive Scan CMOS
- 1080p resolution
- Dual output HD-TVI and 960H BNC
- HD-TVI technology for transmitting full HD-quality video over existing coax cable
- 24 Privacy Masks
- Models include 2 alarm inputs and 1 relay output
- 256 preset positions, 8 preset tours, and 4 shadow tours
- 360° Endless Rotation
- 250°/s Pan Preset Speed and 300°/s Tilt Preset Speed
- Auto-Flip image
- Compatible with GEA and UVP accessories
- Wall bracket to be ordered separately
- EIS (Electronic Image Stabilization)

# TVP-2401

Bevægeligt HD-TVI kamera PTZ, med Zoom 30x optisk (16x digitalt).

## Tekniske specifikationer

### Generelt

Teknologi	HD-TVI-analog
Videostandard	PAL
Privacymaskering	24
Videoudgang	HD-TVI

### Kamera

Sensorstørrelse	1/3"
Maks. opløsning	1080p
Sensorscanning	Progressive
Sensortype	CMOS
Totalt antal piksler (H x V)	1920 x 1080
Effektive pixels (H x V)	1920 x 1080
Digital S/N-forhold	52 dB (AGC OFF)
Lukketid	1/1 to 1/10,000 s, electronic

### Belysningsydeevne

WDR-type	Digital WDR
Digital støjreduktion	3D DNR
Dag nat	True Day/Night
Motoriseret IR-skåret filter	Ja
Farvesensitivitet	0.02 lux @ f1.6 (AGC On)
S / H-følsomhed	0.002 lux @ f1.6 (AGC On)
Infrarød (IR)	Nej

### Linse

Objektivtype	Varifokal motoriseret
Objektivmonteringstype	Camera Block
Brændvidde	4.0 to 120 mm
f-stop	F1.6 to F4.4
Auto iris	Ja
Auto fokus	Ja
Motoriseret zoom	Ja

### Drej / Vip / Zoom

Pande	Pan Manual Speed: 0.1° to 250°/s Pan Preset Speed: 300°/s
Vippe	Tilt Manual Speed: 0.1° to 150°/s Tilt Preset Speed: 200°/s
Uendelig pande	360° endless
Auto flip	Ja
Optisk zoom	30x
Digital zoom	16x
Forudindstillede positioner	256
Forudindstillede ture	8
Skyggeture	4
Understøttede PTZ-protokoller	AD_CODE, BOSCH_CODE, Interlogix RS-485, Pelco-D, Pelco-P

### Alarm I/O

Alarmindgange	2
Alarmuitgangen	1
Alarm I / O-forbindelse	Terminal Type

### Opbevaring

Understøttelse af lokal opbevaring	Nej
------------------------------------	-----

### Video-intelligens

Alarmtrigger	Motion detection, Privacy Masking, Video tampering
Smart event	Defog, Electronic Image Stabilization (EIS)
Intelligent spring	Nej

### Elektrisk

Strømforsyningstype	24 VAC
Strømforsyningsværdi	No PSU included
Strømforsyning	20 W
Nuværende forbrug	1.190 A

### Fysisk

Fysiske dimensioner	220 x 266 mm
Nettovægt	3 kg
Farve	Grå
Form Factor	PTZ
Monter	Pendant mount (requires additional accessory), Wall mount (requires additional accessory)

### Miljø

Vandalt bevis	Ja
Effektvurdering	IK10
Miljø	Udendørs
Driftstemperatur	-30 to +65°C -22 to +149°F
Kold start temperatur	-30°C (-22°F)
IP-vurdering	IP66

### Regulerende

Overholdelse	CE, FCC, HALT, REACH, RoHS, UL, WEEE
--------------	--------------------------------------

### Camera

Resolution	1080p on HD-TVI Output / 960H on BNC
Synchronization system	Internal
Video signal	Dual output HD-TVI and 960H BNC

### Lighting performance

Highlight compensation (HLC)	Yes
------------------------------	-----

### Housing



Rugged	Yes
Cable management	Yes

# TVP-2401

Bevægeligt HD-TVI kamera PTZ, med Zoom 30x optisk (16x digitalt).

## Kompatible produkter

Kategori	Reference	Beskrivelse
Strømforsyning	ATD-6814-PSU	Strømforsyning, 24 V AC / 4 A



Unit: mm



Carrier Fire & Security er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på [dk.firesecurityproducts.com](http://dk.firesecurityproducts.com) eller ved at kontakte din salgsrepræsentant hos.

Last updated on 26 January 2024 - 10:13