

9-30624

AirSense Stratos Standalone Command Module

Description

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

Options Available

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



Einzelheiten

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

9-30624

AirSense Stratos Standalone Command Module

Technische Spezifikationen

Allgemein

Statusanzeige	LED and LCD
Benutzerschnittstelle	Keypad

Elektrische Angaben

Betriebsspannung	21.6 to 26.4 VDC
Aktueller Verbrauch	250 mA

Ausgang

Ausgabemenge	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
--------------	---------------------------------------------------------------

Ausgabebetyp und -Klasse 500 mA @ 30 V

Physikalisch

Abmessungen	427 x 372 x 95 mm (W x H x D)
Nettogewicht	5.2 kg
Farbe	Creme
Montage	Wandmontage
Kabeleinführungen	6 x M20
Material (Körper)	Polycarbonat

Umweltbedingungen

Betriebstemperatur	-10 to +60°C (EN54-20)
Relative Luftfeuchtigkeit	0 to 90% noncondensing
Umgebung	Drinnen
IP Klassifizierung	IP40

Mechanical

Material	Sheet steel enclosure with plastic front cover
----------	------------------------------------------------



Als innovatives Unternehmen behält sich Carrier Fire & Security das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.