TVF-1105

360 IP Dome, 3.0 MPX, Innen, WDR, 1.19mm Fisheye-Objektiv, Echt Tag/Nacht, 10m IR, weiß

Overview

Ideally suited for a variety of applications including retail, commercial, law enforcement and education environments, the TruVision 360º network dome camera provides high-quality image capture, that delivers a complete view of indoor or outdoor areas for exceptional security coverage. Supporting 3MPx sensors, these cameras are PoE 802.3af powered making installation as easy as running a Category 5e cable to the camera location. Particularly effective in areas where a wide area needs to be covered, such as intersecting corridors, parking garages, counters and warehouses. The 360º camera can also be used in a wall-mount configuration to capture panoramic scenes. With an IR range of up to 10m, they can also be used in low-light environments and for 24/7 exterior surveillance. Extra mounting accessories are available for pendant mount and wall mount installation. The cameras can be used with our TruVision NVRs and Prism

Einzelheiten

- 3MPx 1/3" progressive scan CMOS
- Up to 2048 x 1536 real-time streaming
- 360° view angle
- Multiple viewing modes
- Multiple ePTZ streams with preset and patrol functions
- Up to 10m IR range
- 2-way audio, built-in mic and speaker
- Built-in SD/SDHC card slot
- Ceiling, wall and desk mount options
- Indoor version
- Operating temperature range -30 to 60°C

TVF-1105

360 IP Dome, 3.0 MPX, Innen, WDR, 1.19mm Fisheye-Objektiv, Echt Tag/Nacht, 10m IR, weiß

Technische Spezifikationen

Allgemein

Technologie	IP
Videostandard	PAL

Kamera

Sensorgröße	1/3"
Max. Auflösung	3 MPX
Sensor-Scan	Progressiv
Sensortyp	CMOS
Gesamtpixel (H x V)	2048 x 1536
Digitaler Signal/Rauschabstand	50 dB
Verschlusszeit	1/25 to 1/100.000s

Beleuchtungsleistung

WDR	120 dB
Digitale Geräuschreduzierung	3D DNR
Tag / Nacht	Echt Tag / Nacht
Motorized IR Sperrfilter	Ja
Farbempfindlichkeit	0.28lux @(F2.0, AGC ON)
S/W-Empfindlichkeit	0 lux with IR
Infrarot (IR)	Ja
IR-Bereich	10 m
IR-Wellenlänge	850 nm

Codierung

Kompression des Hauptstroms	H.264
Max. Auflösung @ fps	2048 x 1536 @25 fps
High-Frame-Modus unterstützt	50Hz: 1 x fisheye (2048 x 1536, 25fps) or (1536 x 1536, 25fps) or 4 x PTZ (800 x 600, 25fps)

Linse

Objektivtyp	Fest
Brennweite	1.19 mm
f-stop	1.4

Netzwerk

Integration	CGI, ONVIF, PSIA

Audio

Audiokomprimierung	G.711, G.726
Audioeingang	Internal Microphone
Audioausgang	Internal Speaker

Lager

Lokale Speicherunterstützung	Ja
Lokale Speicherunterstützung	Built-in SD/SDHC Slot
Max. Speicherkapazität	64 GB

Video-Intelligenz

Alarmauslöser	Motion detection, Video tampering

Elektrische Angaben

Betriebsspannung	12 VDC
Netzteil	PoE-Eingang
Energieverbrauch	12 W max.
Aktueller Verbrauch	1 A

Physikalisch

Abmessungen	167 x 45 mm
Nettogewicht	767 g
Farbe	Weiß
Formfaktor	360 Grad

Umweltbedingungen

Umgebung	Drinnen
Betriebstemperatur	-30 to +60°C -22 to +140°F

Regulativ

Kompatibilität	C-Tick, CE, FCC, REACH, RoHS, UL, WEEE

Als innovatives Unternehmen behält sich Carrier Fire & Security das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.