6931P

Mini outdoor motion sensor, Dual Technology, 24 GHz

Dual Technology outdoor motion sensor

The Mini Dual variants are outdoor motion sensors and alarm triggers that use two independent passive infrared detectors plus a microwave sensor module. All three sensors must trigger to cause the detector to signal an alarm. They use triple detection technology to deliver precise, reliable presence detection.

Easy and quick to install

Programmable options include a variable pulse count and LED able/disable functionality. Moreover, the integral dual-axis tilt sensor allows 90º of pan and 45º of tilt, which increases the speed of the outdoor installation and provides incredibly accurate aiming of the detection pattern.

Aesthetics and hidden sensor module

The design has a neat appearance that gives no visible indication of the orientation of the detector head and totally hides the wiring. It blends smoothly into residential outdoor applications.



Details

- New outdoor family containing wired PIR, 2 Dual Technology variants and wireless PIR
- Attractive aesthetics
- 14 to 70º detection angle
- 90º pan & 45º tilt for flexible installation
- Sensor module is hidden
- High dust and humidity resistance (IP65)
- 5 years warranty

6931P

Mini outdoor motion sensor, Dual Technology, 24 GHz

Technical specifications

General

Technology	Dual
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No
Processor	Digital microprocessor with nonvolatile memory

Detection

Max. detection range	15 m
Detection range	14 to 70° detection angle, 15 x 13 m
No. of curtains	21
Vertical optical axis adjustment	45° tilt
Horizontal optical axis adjustment	90° pan
Microwave frequency (nom.)	24 GHz
Undercrawl protection	No
Fresnel lens	20 zones for each detection element, which can be masked with the curtain sliders
Microwave module	X-band radar 24 GHz
Customized optics	Double silicon shielded quad element eliminates 50,000 lux of white light
Pulse count	1 or 2

Wired / wireless

Wired / wireless	Wired

Inputs / outputs

Alarm relay characteristic	NC, volt free relay, signal contact 24 VAC/DC @ 50 mA with an integral 25 Ohm series resistor
Outputs	Silent, solid state, magnetically immune. PIR AND Microwave

Electrical

Power supply value	10 to 15 VDC
Current consumption	8 mA (12 V nominal)

Physical

Physical dimensions	71 x 120 x 75 mm (W x H x D)
Net weight	225 g
Shipping weight	325 g
Colour	Bronze
Material	High impact ABS plastic with HDPE cover, UV stabilized
Mounting height	3 to 6 m
Mounting height	Variable up to 6 m / Optimum height 3 m for full range

Environmental

Operating temperature	-30 to +65°C
Environment	Outdoor
IP rating	IP65
Temperature compensation	Analogue (thermistor) and digital sensitivity adjustment

LED indication

	Orange: Microwave activated
	Red: PIR activated
	Orange & Red: Detector alarm

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 June 2026 - 14:50