# ACT745-37

## Proxkey III sitecode 37

### Overview

The new ProxKey III Proximity Keyfob incorporates proximity technology into a device approximately the size of an automotive key. Small and convenient, the Keyfob is always there when you need it, on your key ring.

### Features

HID's advanced technology allows the Keyfob to be programmed with up to 37 bits of Wiegand formatted information for universal compatibility with all Wiegand reader applications. The new keyfob can accommodate an external number for easy identification and control.




### Details

- Offers universal compatibility with all HID proximity readers
- Can be placed on a key ring for convenient entry
- Provides an external number for easy identification and control
- HID standard 32-bit configuration

# ACT745-37

## Proxkey III sitecode 37

## Technical specifications

### System

| | |
|---|---|
| Supported readers | HID Proximity Readers |

### Technology

| | |
|---|---|
| Credential type | Proximity |
| Credential driftsfrekvens | 125 KHz |

### Physical

| | |
|---|---|
| Form factor | Key Fob |
| Physical dimensions | 48 x 23 x 9 mm (H x W x D) |
| Net weight | 7.3 g |

### Environmental

| | |
|---|---|
| Operating temperature | -45 to +70°C |
| Relative humidity | 5 to 95% noncondensing |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 March 2024 - 10:13