ATS1621

ATS Smart Card programmer (European plug)

Product Overview

With this card programmer connected to a PC running TITAN, the installer, service provider and/or customer may program and re-program Smart Cards any number of times, and issue those cards to Users at their site/s.
No more having to order a pre-set minimum number of ""site coded"" and ""sequenced"" cards for your site and experiencing delays of weeks. Just bring up the ""User"" screen in TITAN and as the Users are created or edited, simply hit the ""Write"" button, present a card to the programmer and the Smart Card is instantly programmed for that specific User's Function.

Connection

When connecting the ATS1621 to a PC running Titan, you need to choose a Com port that has been designated as a Card Programmer Port. If no port has been designated as a Card Programmer port, then you need to identify a Com port (using the port as set-up in Admin - Connection Links) that will be specified as a card programmer port.

Connection password

To protect from programming unauthorised cards, each time Titan connects to the card programmer you need a connection password. This password can be any numeric password up to 10 characters in length.



Details

- European plug
- RS232 connection
- Compatible with Titan programming package
- Program all ATS proximity cards and keyfobs

ATS1621

ATS Smart Card programmer (European plug)

Technical specifications

Technology

Credential type	Proximity
Credential driftsfrekvens	125 KHz
Supported technology 125 kHz	HiTag 2

Physical

Form factor	CR80 (Credit)
Physical dimensions	147 x 77 mm

Environmental

Operating temperature	+10 to +50°C

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:32