# BS111N

**Battery, 6 V, 10 Ah**




## Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS111N

## Battery, 6 V, 10 Ah

## Technical specifications

### General

| | |
|---|---|
| Product type | Sealed lead acid battery |

### Electrical characteristics

| | |
|---|---|
| Nominal voltage | 6 V |
| Nominal capacity | 10 Ah |
| Internal approx. resistance | 7 mOhm |

### Charge / discharge

| | |
|---|---|
| Max. charge voltage | 6.9 VDC at +20°C |
| Max. charge current | 3 A |
| Max. discharge current | 50 A |

### Physical

| | |
|---|---|
| Physical dimensions | 151 x 50 x 94 mm |
| Net weight | 2.082 kg |
| Shipping weight | 2.082 kg |
| Colour | Dark grey |
| Material | ABS |
| Terminal type | Fast-on 4.8 mm |

### Environmental

| | |
|---|---|
| Fire retardant | No |
| Vandal proof | No |
| Operating temperature | 0 to +40°C |
| Storage temperature | -15 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS 2, WEEE |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:53