BS121N

Battery, 12 V, 1.2 Ah, Interlogix

Product overview

Sealed lead acid battery 12 V, 1.2 Ah with Fast-on 4.8 mm terminal type.



Details

- Maintenance free 12 VDC
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS121N

Battery, 12 V, 1.2 Ah, Interlogix

Technical specifications

General

Product type	Battery pack, NiCd battery, Sealed lead acid battery

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	1.2 Ah
Internal approx. resistance	75 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	0.36 A
Max. discharge current	6 A

Physical

Physical dimensions	97 x 43 x 53 mm
Net weight	0.596 kg
Shipping weight	0.596 kg
Material	Metal
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:33