BS133N

Battery, 12 V, 65 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS133N

Battery, 12 V, 65 Ah

Technical specifications

General

Product type	Sealed lead acid battery

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	65 Ah
Internal approx. resistance	10 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	19.5A
Max. discharge current	325 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	350 x 166 x 174 mm
Net weight	23.0 kg
Shipping weight	23.0 kg
Material	ABS
Terminal type	MS bolt & nuts

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 March 2026 - 14:03