# CV2106

## Cavius wireless photoelectric smoke alarm, battery powered, 10 years service life, 10 years sealed-in battery,

### Product overview

Optical smoke alarm device with wireless interlink. Designed for installation in the home, mobile homes and caravans.

This 78 mm smoke alarm can be connected with other alarms from the CAVIUS Wireless alarm family or function as a stand alone alarm.




### Details

- Optical smoke alarm sensor technology
- 10 years sealed in battery - replacement not required for a full duration of the service life
- Build in RF - connectable with up to 32 units (Cavius Wireless Alarms Family)
- Smoke chamber Dual Mesh System and Dust Compensation - for better sensing and nuisance alarms reduction
- Suitable for mobile homes and caravan installation
- Large Test / Hush Button
- 10-year warranty

# CV2106

## Cavius wireless photoelectric smoke alarm, battery powered, 10 years service life, 10 years sealed-in battery,

## Technical specifications

### General

| | |
|---|---|
| Status indication | Sound output level: 85 dB(A) at 3 m, red LED indicator |
| User interface | Red LED indicator, Test/Hush center button, Learn mode button |
| Wireless frequency | 868 MHz |
| Compatibility | Cavius Wireless Alarm Family |
| Event log | No |
| Chart record | No |
| Connectivity | Build in Wireless RF, max. connection capacity up to 32 units |

### Electrical

| | |
|---|---|
| Power supply type | Batteries |
| Batteries | Sealed-in lithium, 10 years battery life |
| Operating voltage | 3 VDC |

### Physical

| | |
|---|---|
| Physical dimensions | 78 x 41 mm (D x H) |
| Net weight | 96 g |
| Colour | White |
| Mounting type | Ceiling mount, Wall mount |

### Environmental

| | |
|---|---|
| Operating temperature | +4 to +38ºC (tested from 0 to +55°C) |
| Storage temperature | -20 to +60ºC |
| Relative humidity | Operating: up to 90%, noncondensing<br>Storage: up to 93%, noncondensing |

### Regulatory

| | |
|---|---|
| Certification | CE, EN14604 |




Kidde

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 8 January 2024 - 8:38