DB961

950 Series Isolating Base

General

The DB961 is a 900 series addressable base with built in loop isolator. This isolating base senses and isolates short circuit faults on 900 series loops. Up to 20 addressable devices may be placed between any two isolator bases.

Installation

The DB961 uses the standard passive address card for a unique device address assignment. It is polarity sensitive and loop powered. It is compatible with both 950 and 990 series devices.

Operation

In short circuit conditions, the integral yellow LED on the DB961 is illuminated. The detector inserted in the base remains operational under short circuit conditions. Power and communications to the affected section are restored automatically when the fault is cleared.



Details

- Passive base address
- Programmable slide-in address card
- Aesthetic design
- Multiple European approvals

DB961
950 Series Isolating Base

Technical specifications

General

Status indication	Yellow LED

Electrical

Operating voltage	17 VDC (min.supply voltage) 28 VDC + 9 VDC comms. (max. supply voltage)
Current consumption	23 µA, operating current @ 18 VDC 43 µA, operating current @ 28 VDC 4 mA, operating current, isolated 1 A, line current (max.) 3 A, line current (to isolation)

Physical

Physical dimensions	100 x 24 mm (Ø x H)
Net weight	100 g

Environmental

Operating temperature	-20 to +60°C
Storage temperature	-30 to +80°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor

Regulatory

Certification	EN54-17, EN54-5, EN54-7

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 February 2025 - 11:37