RF903I4

Acoustic glassbreak Detector RF433 MHz



Details

- Provides 360-degree coverage
- Can be mounted on a ceiling, opposite wall or adjacent walls
- Range of up to 6 meters

RF903I4

Acoustic glassbreak Detector RF433 MHz

Technical specifications

General

Technology	Acoustic
Range	Max. 6 m radius for glass panes of at least 0.5 x 0.6 m
Tamper switch	Yes
Glass types and thickness	Plate : 2.4 to 6.4 mm / Tempered : 3.2 to 6.4 mm / Laminated : 3.2 to 6.4 mm

Wired / wireless

Wired / wireless	Wireless
Wireless frequency	433 MHz legacy
Open-air range	150 m

Electrical

Operating voltage	2.6 to 4.5 VDC
Current consumption	26 µA typical average
Batteries	2 x 3.0 V Lithium DL123A
Battery lifetime	5 years
Maximum power output	10 dBm e.r.p.
Transmitter conditions	Alarm, tamper and low battery supervisory

Physical

Physical dimensions	108 x 79 x 31 mm
Colour	White
Mounting type	Surface mount

Environmental

Operating temperature	0 to 50°C
Storage temperature	-34 to +60°C
Relative humidity	90%

Regulatory

Compliancy	CE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:23