

SC-32-0120-0001-99

SmartCell Red Sounder and Wall-Beacon (VAD White Flash)



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-32-0120-0001-99 SmartCell Red Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

Wireless frequency	868 MHz
Electrical	
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride
E accertes	batteries (Fanso or Titus)
Sounder	
Output level	95 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32
VAD	
Colour	white flash
Rating	W-2.4-6
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
Physical	
Physical dimensions	110 x 77 mm (Ø x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount
Mounting position	Wall
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)
	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
IP rating	IP21C
Regulatory	
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-23



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.