# TESTIFIRE-XTR2-HEAD

## All-in-one connected smoke/heat detector test head

### Powerful insights, automated test reports & records

The Testifire-XTR2 combines testing and reporting to deliver on compliance, giving service companies and building owners the insight and assurance they demand. The Testifire-XTR2 is designed to work with all detector brands and models, and with both addressable and conventional systems.

### Test modes

The Testifire-XTR2 supports all-in-one smoke and heat testing including smoke only, heat or hi-heat only, combined and sequential smoke/heat as well as ASD test compatibility.

### DT Connect App

Every Testifire-XTR2 includes a 6-month trial of DT Connect premium. When the 6-month trial period ends, a DT Connect subscription is needed to continue accessing the full range of features. The Testifire-XTR2 can also be used without subscription, albeit with limited features.

DT Connect alongside the Testifire-XTR2, allows advanced features to streamline the testing process, easily manage site assets and optimise reporting capability by automatically generating test reports.

DT Connect allows for:
• Minimising time spent on basic tasks
• Panel time logging to synchronise test and panel event timestamps *
• Test result capturing
• Asset identification *
• Panel reconciliation *
• Job summary
• Shareable reports *
* Premium DT Connect features

### Product information

The Testifire-XTR2 head includes:

1 x TESTIFIRE-XTR2-HEAD
1 x TESTIFIRE-MEM Membrane 90 mm dia



### Details

- Rapid smoke generation saves waiting time
- 50% faster heat and hi-heat activation compared with the legacy TM010
- Sequential & combined test modes including hi-heat testing up to 100°C
- TFT-LCD full colour touch screen user interface
- Automatic LED torch in dark environments
- Automatic test result capture with detector LED recognition support
- Clearing mode to prevent re-alarms
- Robust and repairable
- Bluetooth enables communication to the DT Connect App with 6-month free PREMIUM support
- Optional subscription for premium features in the DT Connect app and Cloud Portal

# TESTIFIRE-XTR2-HEAD

**All-in-one connected smoke/heat detector test head**

## Technical specifications

### Electrical

| | |
|---|---|
| Power supply type | Batteries |
| Operating voltage | 10.8 V (35.1 wh / 3250 mAh) |
| Current consumption | < 0.5 A rms (smoke testing)<br>4 to 6 A rms (heat testing) |
| Battery type | Lithium Ion |
| Charging | USB-C connection to charging cradle |

### Physical

| | |
|---|---|
| Physical dimensions | 406 x 156 x 150 mm |
| Net weight | 1.25 kg |
| Shipping weight | 2.39 kg |
| Colour | Black, Grey |
| Stimulus type | Cartridge |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | 5 to 45°C (41 to 113°F) - Head unit<br>5 to 40°C (41 to 104°F) - Charger cradle |
| Storage temperature | -10 to 50°C (14 to 122°F) |
| Relative humidity | 0 to 85% non-condensing - operating<br>0 to 90% non-condensing - storage |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CE |

### SKU info

| | |
|---|---|
| Product brand | testifire |

### Test

| | |
|---|---|
| Carbon Monoxide | No |
| Heat | Yes |
| Smoke | Yes |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Test Equipment | CB001 | |
| Test Equipment | ET010 | |
| Test Equipment | TES3-6PACK | |
| Test Equipment | TESTIFIRE-ADAP | |
| Test Equipment | TESTIFIRE-BP | |
| Test Equipment | TESTIFIRE-CHAK | |
| Test Equipment | TESTIFIRE-GEN-1PK | |
| Test Equipment | TESTIFIRE-MEM | |
| Test Equipment | TESTIFIRE-MEML | |
| Test Equipment | TESTIFIRE-SOP | |
| Test Equipment | TESTIFIRE-XTR2 | |
| Test Equipment | TESTIFIRE-XTR2-6M | |

EDWARDS
*Built for Resilience*

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 October 2024 - 13:14