

FCX-191-200

Fusion Wireless Detector Base w/ Sounder & Red VID

General

The FCX-191-200 is a wireless detector base with built in sounder (FAD) and visual indicator (VID) for use with point type, Fusion wireless detectors. It is ideal for applications where cable interface is difficult to manage or impossible to achieve.

The base connects wirelessly to the Fusion interface unit, which in turn transmits the wireless detector signal to the fire panel hardware loop.

The Range

The Fusion series consists of:

- Optical Smoke Detectors
- Multisensor Smoke Detectors
- A1R Heat Detectors
- CS Heat Detectors
- Sounders in red and white
- Combination Sounder VIDs and VADs
- Manual Call Points
- Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from its base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



Details

- Easy to install
- Electronic addressing
- Self-monitoring
- Proven technology
- Eliminates cable installation problems
- Uses 868 MHz radio channels

FCX-191-200

Fusion Wireless Detector Base w/ Sounder & Red VID

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	Fusion gateway FCX-532-001

Electrical

Power supply type	Batteries
Batteries	3x AA Alkaline (Panasonic LR6AD Powerline / Varta 4006 Industrial) 3x C Alkaline (Panasonic LR14AD Powerline / Varta 4014 Industrial)
Power consumption	< 1 W
Operating voltage	3.5 to 4.5 VDC
Current consumption	0.2 to 300 mA
Output transmitter power	0 to 25 mW

Sounder

Output level	< 87 dB(A) @ 1 m
Output level adjustment	13 dB
Frequency	Selectable
Selectable tones	4
No. of stages	2

VID

Colour	White
--------	-------

Physical

Physical dimensions	146 x 53 mm (Ø x d)
Colour	White
Mounting type	Ceiling mount
Mounting position	Ceiling

Environmental

Vandal proof	No
Operating temperature	-10°C to 55°C
Storage temperature	5°C to 30°C
Relative humidity	< 95% non-condensing
Environment	Indoor
IP rating	IP23

Regulatory

Compliance	CE, REACH, RED (2014/53/EU), RoHS 2, WEEE
Certification	BOSEC, CPR
Standards	EN54-3



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 12:23