

RS-3241

UltraSync Doorbell Camera

Overview

The UltraSync Doorbell Camera from Interlogix brings state of the art, high-definition images to the residential security segment. Designed specifically for use with the UltraSync series of smart security products, the UltraSync Doorbell camera offers live video, two-way audio, motion detection and clip recording. It connects and rings the existing mechanical doorbell chime when the doorbell button is pressed. The camera can be triggered by an intrusion event and managed through the UltraSync mobile application.

Connectivity

The UltraSync Doorbell Camera is based on the Wi-Fi standards of IEEE802.11b/g/n and operates in the 2.4GHz range. Transmission rates of up to 150 Mbps are supported, and secure wireless communication is achieved via WPA2-PSK and WPS wireless encryption standards.

Installation

Setup and configuration are simplified using the UltraSync mobile application. Onboard storage, via micro SD card, adds recorded clips without the need for NVRs or cloud storage. The UltraSync Doorbell Camera is designed specifically for outdoor residential applications. Three interchangeable faceplates and two angles brackets for optimized mounting are included.



Details

- Video / Audio: Compatible with UltraSync series products by Interlogix 1080p resolution H.264 compression technology with dual-streaming capability 180° ultra-wide field of view Built-in speaker and omnidirectional microphone
- Video Enhancement: WDR and/or real-time video streaming up to 1080p resolution to capture every detail Day/night functionality and infrared illuminator for capturing images in various lighting scenarios. Up to 5 meters IR range - with on/off settings
- Video alarms: Motion Detection
- Recorded clips stored onboard using a micro SD/SDXC card. 16 GB card included
- Supports IEEE802.11b/g/n Wi-Fi standards Frequency range 2.4 GHz Encryption security support for WPA2-PSK and WPS wireless encryption standards.
- Environment and Installation Support majority of mechanical doorbell chime Using existing 16-24VAC doorbell wire power 3 interchangeable color faceplates (pearl, silver and carbon). Fast and simple integration into UltraSync app using camera scan feature

RS-3241

UltraSync Doorbell Camera

Technical specifications

General

Accessory group	ZeroWire
Type	Accessory

Electrical

Power consumption	14.4 W (Max.)
Operating voltage	16 to 24 VAC
Current consumption	400 mA

Physical

Physical dimensions	46 x 122 x 28 mm
Net weight	142 g
Shipping weight	160 g
Colour	Silver
Material	ABS

Environmental

Operating temperature	-30 to 50 °C
Storage temperature	-20 to 70 °C
Environment	Indoor, Outdoor

Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	UL



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 September 2023 - 16:22