

# ACL800SUW-RDMF-S

## ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, SILVER

### Product description

---

These surface mount ACL800SUW-RDMF readers includes a buzzer and a tri-color LED for state indication (access granted, access denied or idle). The ACL800SUW-RDMF has an automatic Wiegand output (32 or 56 bit) and is capable of reading Mifare cards/fobs (13.56 MHz).

### The ACL800 range

---

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.

### Card technology

---

The readers are compatible with TruPortal MIFARE Classic, - Plus, - Ultralight and - DESFire EV1/EV2. These technologies use the CSN (Card Serial Number) or UID (Unique Identifier) as credential identifier. The wiegand output (32 or 56 bit) is automatic according to the card type and ensures uniqueness of the MIFARE CSN with 4 and 7 Byte UID.

### Compatibility

---

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.



### Details

---

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Compatible with the TruPortal learn-in reader (TP-RDR-LRN)
- Backlight illumination
- 13.56 MHz Mifare Reader

# ACL800SUW-RDMF-S

## ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, SILVER

### Technical specifications

---

#### System

---

Max. reader distance to panel 50 m

---

CSN (Card Serial Number) Yes

---

No. of LEDs 3

---

Language installation manual English

---

#### Technology

---

Reader type Smart Card

---

Reader operating-transmitting frequency 13.56 MHz

---

Supported technology 13.56 MHz MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE UltraLight (CSN)

---

Mifare type ISO14443A

---

No. of Mifare bytes CSN 4 Bytes (S50), 7 Bytes (S70)

---

#### Interface & connections

---

Interface Wiegand

---

Connector type Pigtail, Terminal strip

---

Pigtail length 100 cm

---

#### Tamper type

---

Pry-off tamper No

---

Opening tamper Yes

---

#### Operation

---

Stand-alone No

---

PIN keypad No

---

#### Electrical

---

Power supply type VDC

---

Power supply value 9 to 14 VDC

---

Current consumption 150 mA at 12 VDC max

---

#### Physical

---

Physical dimensions 92 x 51 x 27 mm

---

Net weight 160 g

---

Shipping weight 260 g

---

Colour Silver

---

Material Moulded aluminium

---

Form factor Mullion

---

Mounting type Surface mount

---

#### Environmental

---

Environment Indoor, Outdoor

---

Operating temperature -20 to +50°C

---

Storage temperature -20 to +50°C

---

Relative humidity 5% to 93% RH noncondensing

---

#### Regulatory

---

Compliance CE, RoHS

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 6 September 2023 - 12:24