

FE240

Door Holder, Flush Mounting, 400N

General

The FE240 is a flush mount door holder, with a Bayblend housing, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE240 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE240

Door Holder, Flush Mounting, 400N

Technical specifications

General

Release button	No
----------------	----

Electrical

Power supply type	24 VDC
-------------------	--------

Physical

Physical dimensions	85 x 85 x 35 mm
---------------------	-----------------

Compatible products

Category	Reference	Description
Door Holders	FE225-150	Universal Bracket Wall or Floor Mounting - 150 mm
Door Holders	FE225-300	Universal Bracket Wall or Floor Mounting - 300 mm
Door Holders	FE527	Standard Anchorplate for FE500 Series Magnets
Door Holders	FE529	Swivel Anchorplate for FE500 Series Doormagnets



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 15 February 2024 - 9:57