

# FE560

### Door Holder, Universal Adjustable Tube, VDS Magnet

#### General

The FE560 is a VdS approved door holder with a universal adjustable tube with a reach of between 156.5 and 175 mm when used in 180°C configuration and between 125 and 150 mm used in 90° configuration. It is normally very well suited for applications where the height of the magnet may need adjustment to suit the conditions. It may be used in floor, ceiling or wall mount applications, and is supplied with a manual release button.

#### A magnet for all occasions

The FE500 series door holding magnets are the result of years of specialised development. Rated at just 1.5 W @ 24VDC, these powerful magnets pack a holding power of 490 N. The FE560 has a spring-loaded pin to ensure ejection against remnant magnetism.

#### **Application friendly**

The FE500 series offer cost effective solutions without sacrificing performance. Reinforced aluminium gives it a smart look and rugged endurance, whilst reinforced wall mount aluminium extensions allow up 175 mm distance from the wall. Keeper plates are not supplied with the magnet and can be ordered seperately according the application.

#### Installer friendly

For practical ease of installation, all units are complete with electrical terminations. Protection diodes prevent electromagnetic pulses and reverse polarity protection, and speeds up installation. The mountings are predrilled in a practical, standard format for rapid mounting.

### **Approvals**

All models are VdS approved.



#### **Details**

- · Wall, floor or ceiling mount
- Low power 1.5 W
- 490 N holding power on VDS coils
- 100% duty cycle
- Anti-remnant ejector
- Protection diode and reverse polarity protection
- Release button
- VdS Approved (see specification)

# FE560

Door Holders

FE529

# Door Holder, Universal Adjustable Tube, VDS Magnet

## **Technical specifications**

General					
Holding force N	l (Newto	า)490			
Release button		Yes			
Reverse polarity protection		Yes (diode)			
Electrical					
Power supply type		24 VDC			
Power consumption		1.5 W	1.5 W		
Current consumption		62.5 mA			
Physical					
Physical dimensions		125 to 150 x 92.5 mm (mounting @ 90° H x W) 156.5 to 175 x 70 mm (mounting @ 180° L x Ø)			
Cable entries		-			
Environmer	ntal				
IP rating		IP42			
Regulatory					
Certification		VdS			
Compatible	produc	ets			
Category	Refere	ence	Description		
Door Holders	FE527		Standard Anchorplate for FE500 Series Magnets		

Swivel Anchorplate for FE500 Series

Doormagnets



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.