

TVB-2401

TruVision HD-TVI Analog Bullet Camera, PAL, 720P, 3.6mm lens, true D/N, DWDR, 20m IR, HD-TVI output, Coax OSD control, 12VDC, IP66

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



TVB-2401

TruVision HD-TVI Analog Bullet Camera, PAL, 720P, 3.6mm lens, true D/N, DWDR, 20m IR, HD-TVI output, Coax OSD control, 12VDC, IP66

Technical specifications

General

| | |
|----------------|---------------|
| Technology | HD-TVI analog |
| Video standard | PAL |

Camera

| | |
|-----------------|-------------|
| Max. resolution | 720p |
| Sensor scan | Progressive |
| Sensor type | CMOS |

Lighting performance

| | |
|-------------------------|----------------|
| WDR | DWDR |
| Day / night | True Day/Night |
| Motorized IR cut filter | Yes |
| Infrared (IR) | Yes |

Lens

| | |
|-----------|-------|
| Lens type | Fixed |
|-----------|-------|

Network

| | |
|-------------|------------------|
| Integration | CGI, ONVIF, PSIA |
|-------------|------------------|

Physical

| | |
|---------------------|---------------------|
| Physical dimensions | 70 x 150 mm |
| Net weight | 291 g |
| Colour | Grey (Pantone 428c) |
| Form Factor | Bullet |

Environmental

| | |
|-----------------------|------------------------------|
| Environment | Outdoor |
| Operating temperature | -30 to 60°C |
| Storage temperature | -20 to +70°C -4 to +158°F |

Regulatory

| | |
|------------|--|
| Compliance | C-tick, CE, FCC, REACH, RoHS, UL, WEEE |
|------------|--|



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 December 2023 - 17:54