

TVB-2402

TruVision HD-TVI Analog Bullet Camera, PAL, 720P, 2.8 to 12mm lens, true D/N, DWDR, 40m IR, Dual output 960H or HD-TVI, Coax OSD control, 12VDC/24VAC, IP66

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Details

- 720p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 40 m
- IP66 environmental rating
- Digital wide dynamic range
- 2.8 to 12 mm lens
- Dual power 12 VDC / 24 VAC
- Bracket included
- Provide OSD control via TruVision up the coax and built-in menu button

TVB-2402

TruVision HD-TVI Analog Bullet Camera, PAL, 720P, 2.8 to 12mm lens, true D/N, DWDR, 40m IR, Dual output 960H or HD-TVI , Coax OSD control, 12VDC/24VAC, IP66

Technical specifications

General	
Technology	HD-TVI analog
Video standard	PAL
Camera	
Sensor size	1/3"
Max. resolution	720p
Sensor scan	Progressive
Sensor type	CMOS
Lighting performa	nce
WDR type	Digital WDR
Day / night	True Day/Night
Motorized IR cut filter	Yes
Infrared (IR)	Yes
IR range	40m
Lens	
Lens type	Varifocal
Network	
Integration	CGI, ONVIF, PSIA
Physical	
Colour	Grey
Form Factor	Bullet
Environmental	
Environment	Outdoor
Regulatory	
Compliancy	C-tick, CE, FCC, REACH, RoHS, UL, WEEE





As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.