

# TVM-2202 TRUVISION 22" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

### Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market.

Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

#### Capabilities

The TVM-2202 is a 22" class monitor, offering HDMI, VGA and BNC connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



#### **Details**

- 22" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI
- BNC analog input

## TVM-2202 TRUVISION 22" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Regulatory Compliancy

CE

### **Technical specifications**

General		
Technology	LED	
VESA compatibility	100 x 100 mm	
Filter type	3D Combfilter, Deinterlace	
ncluded accessories	Manual, Power Adapter, Power Cord	
Panel lamp life	30,000 hours	
Display		
Screen size	21.5"	
Aspect ratio	16:9	
Contrast ratio	1000:1	
Viewing angle (H/V)	170° / 160°	
Response time	5ms	
Brightness	250 cd/m² (typ)	
Compatible video standards	NTSC/PAL Auto Detect	
Recommended	1920 x 1080 @ 60 HZ	
resolution		
Audio		
Speaker power	2W x 2	
Speakers	Built-in	
Interface		
BNC video I/O	1/1	
/GA video in	Yes	
HDMI video in	1	
RCA audio in	1	
PC stereo in	Yes	
	No	
	NO	
Operations		
Controls	Power, Up/Down, Left/Right, Source, OSD Menu	
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish	
Remote control support	No	
Electrical		
Power supply type	100 to 240 VAC	
Power consumption	<30W	
Physical	540-mm V 200-mm V 202	
Physical dimensions	542mm X 368mm X 207mm	
Net weight	4.0 kg	
Shipping weight	5.8 kg	
Colour	Black	
Housing type	Plastic	
Environmental		
Operating temperature	0 to 40°C	
Storage temperature	-20 to 60°C	
storage temperature		
Relative humidity	10 to 85%	

	313 312 312.3 317.2	45.5 73.7
--	---------------------	-----------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.