

TVM-2212 TRUVISION 22" LED, VGA, HDMI, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market.

Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

Capabilities

The TVM-2212 is a 22" class monitor, offering HDMI and VGA connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



Details

- 22" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including VGA, HDMI

TVM-2212 TRUVISION 22" LED, VGA, HDMI, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Regulatory Compliancy

CE

Technical specifications

General	LED			
Technology	LED			
VESA compatibility	100 x 100 mm 3D Combfilter. Deinterlace			
Filter type				
Included accessories	Manual, Power Cord, Remote Control			
Panel lamp life	30,000 hours			
Display				
Screen size	21.5"			
Aspect ratio	t ratio 16:9			
Contrast ratio	ast ratio 1000:1			
Viewing angle (H/V)	g angle (H/V) 170° / 160°			
Response time	5ms			
Brightness	ness 250 cd/m² (typ)			
Compatible video	NTSC/PAL Auto Detect			
standards				
Recommended	1920 x 1080 @ 60 HZ			
resolution				
Audio				
Speaker power	2W x 2			
Speakers	Built-in			
Interface				
BNC video I/O	No			
VGA video in	Yes			
HDMI video in	1			
RCA audio in	1			
PC stereo in	Yes			
	No			
Operations				
Controls	Power, Up/Down, Left/Right, Source, OSD Menu			
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish			
Remote control support	No			
Electrical				
Power supply type	100 to 240 VAC			
Power consumption	<30W			
Physical				
Physical dimensions	512mm x 372mm x 150mm			
Net weight	3.9 kg			
Shipping weight	5.3 kg			
Colour	Black			
Housing type	Plastic			
5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5				
Environmental				
	0 to 40°C			
Environmental	0 to 40°C -20 to 60°C			
Environmental Operating temperature				

	313	



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.