

TVM-2702

TRUVISION 27" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market.

Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

Capabilities

The TVM-2702 is a 427" class monitor, offering HDMI, VGA and BNC connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



Details


- 27" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI
- BNC analog input

$\begin{tabular}{l} TVM-2702\\ \hline \textbf{TRUVISION 27" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080\\ \hline \end{tabular}$

Technical specifications

General			
Technology	LED		
VESA compatibility	100 x 100 mm		
Filter type	3D Combfilter, Deinterlace		
Included accessories	Manual, Power Adapter, Power Cord, Remote Control		
Panel lamp life	30,000 hours		
Display			
Screen size	27"		
Aspect ratio	16:9		
Contrast ratio	1,000:1		
Viewing angle (H/V)	170° / 160°		
Response time	8ms		
Brightness	300 cd/m² (typ)		
	NTSC/PAL Auto Detect		
Compatible video standards	NTSC/PAL Auto Detect		
Recommended	1920 x 1080 @ 60 HZ		
resolution			
Audio			
Speaker power	2W x 2		
Speakers	Built-in		
Interface			
BNC video I/O	1/1		
VGA video in	Yes		
HDMI video in	1		
RCA audio in	1		
PC stereo in	Yes		
Audio out	No		
Onematican			
Operations Controls	Power, Up/Down, Left/Right, Source, OSD Menu		
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish,		
Remote control support	Polish Yes		
- Support	103		
Electrical			
Power supply type	100 to 240 VAC		
Power consumption	<40W		
Physical			
Physical dimensions	647mm x 447 mm x 249mm		
Net weight	4 kg		
Shipping weight	6.5 kg		
Colour	Black		
Housing type	Plastic		
Environmental			
Operating temperature	0 to 40°C		
Storage temperature	-20 to 60°C		
Relative humidity	10 to 85%		
	10 (0 03 /0		

Regulatory		
Compliancy	CE	





Indoor

Environment

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.