



## 1386-LGGMN

**ISO Prox II Graphics Quality Both Sides - standard card includes, 26 bit format, plain white glossy finish for direct card printing on front and back, printed ID number and No gaps in**



# 1386-LGGMN

ISO Prox II Graphics Quality Both Sides - standard card includes, 26 bit format, plain white glossy finish for direct card printing on front and back, printed ID number and No gaps in

## Technical specifications

---

### System

Reading distance	more than 20 cm
Card slot punch	No

### Technology

Credential type	Proximity
Credential driftsfrekvens	125 KHz
Support technology	125 HID Prox KHz

### Printing

Direct surface printing	Yes
Thermal transfer printing	Not recommended

### Ordering information

Minimum order quantity	100
Special card order form required	Yes

### Physical

Surface cover	Glossy
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	5 g
Shipping weight	20 g
Colour	White

### Environmental

Operating temperature	-45 to 70°C
Storage temperature	-45 to 70°C
Relative humidity	5 to 95% noncondensing

### Regulatory

Compliance	RoHS
------------	------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [uk.firesecurityproducts.com](http://uk.firesecurityproducts.com) online or contact your sales representative.

Last updated on 21 May 2024 - 13:10